

**SANYO**

No.1784B

**2SB1118/2SD1618**

PNP/NPN Epitaxial Planar Silicon Transistors

Low-Voltage, High-Current Amp,  
Muting Applications**Features**

- Low collector-to-emitter saturation voltage.
- Very small size making it easy to provide high-density, small-sized hybrid IC's

( ): 2SB1118

**Absolute Maximum Ratings at Ta=25°C**


			unit
Collector to Base Voltage	$V_{CBO}$	(-)20	V
Collector to Emitter Voltage	$V_{CEO}$	(-)15	V
Emitter to Base Voltage	$V_{EBO}$	(-)5	V
Collector Current	$I_C$	(-)0.7	A
Collector Current(Pulse)	$I_{CP}$	(-)1.5	A
Collector Dissipation	$P_C$	500	mW
	$P_C$ Mounted on ceramic board (250mm <sup>2</sup> x 0.8mm)	1.3	W
Junction Temperature	$T_j$	150	°C
Storage Temperature	$T_{stg}$	-55 to +150	°C

**Electrical Characteristics at Ta=25°C**









			min	typ	max	unit
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = (-)15V, I_C = 0$			(-)0.1	μA
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = (-)4V, I_C = 0$			(-)0.1	μA
DC Current Gain	$h_{FE}(1)$	$V_{CE} = (-)2V, I_C = (-)50mA$	140		560*	
	$h_{FE}(2)$	$V_{CE} = (-)2V, I_C = (-)500mA$	60			
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10V, I_C = (-)50mA$		250		MHz
C-E Saturation Voltage	$V_{CE(sat)}^1$	$I_C = (-)5mA, I_B = (-)0.5mA$		10	25	mV
	$V_{CE(sat)}^2$	$I_C = (-)100mA, I_B = (-)10mA$		(-15)	(-35)	mV
				30	80	mV
				(-60)	(-120)	mV
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)100mA, I_B = (-)10mA$		(-)0.8	(-)1.2	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10μA$		(-)20		V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1mA$		(-)15		V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10μA$		(-)5		V
Output Capacitance	$c_{ob}$	$V_{CB} = (-)10V, f = 1MHz$		8		pF
				(13)		pF


\*:The 2SB1118/2SD1618 are classified by 50mA  $h_{FE}$  as follows:

140	S	280	200	T	400	280	U	560
-----	---	-----	-----	---	-----	-----	---	-----

Marking 2SB1118:BA  
2SD1618:DA $h_{FE}$  rank :S,T,U**Package Dimensions 2038**  
(unit:mm)E: Emitter  
C: Collector  
B: BaseSANYO: PCP  
(Bottom View)**SANYO Electric Co., Ltd. Semiconductor Business Headquarters**  
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

# 2SB1118/2SD1618





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.