

Features


- Avalanche rugged technology.
- Low input capacitance.
- Improved gate charge.
- Low leakage current : 10uA (Max.) @ $V_{DS}=500V$.
- Low $R_{DS(ON)}$: 1.17 Ω (Typ.)

Ordering Information

Type NO.	Marking	Package Code
STK830F	STK830	TO-220F

Outline Dimensions

unit : mm



Absolute maximum ratings

Characteristic	Symbol	Rating	Unit
Drain-Source voltage	V_{DSS}	500	V
Gate-Source voltage	V_{GS}	± 30	V
Continuous Drain current ($T_c=25^\circ\text{C}$)	I_D	4.5*	A
Continuous Drain current ($T_c=100^\circ\text{C}$)	I_D	2.9*	A
Drain Current-Pulsed ①	I_{DM}	18	A
Power Dissipation ($T_c=25^\circ\text{C}$)	P_D	38	W
Linear Derating Factor		0.3	W/ $^\circ\text{C}$
Single Pulsed Avalanche Energy ②	E_{AS}	270	mJ
Avalanche current ①	I_{AR}	4.5	A
Repetitive Avalanche Energy ①	E_{AR}	7.3	mJ
Peak Diode Recovery dv/dt	dv/dt	5.5	V/ns
Operating Junction and Storage temperature range	T_J, T_{stg}	-55~150	$^\circ\text{C}$
Maximum lead temp. for soldering Purpose, 1/8" from case for 5-seconds	T_L	300	$^\circ\text{C}$

* Limited by Maximum junction Temperature

Thermal Resistance

Characteristic	Symbol	Typ.	Max	Units
Junction-to-Case	$R_{\theta JC}$		3.31	$^\circ\text{C}/\text{W}$
Case-to-Sink	$R_{\theta CS}$	0.5		
Junction-to-Ambient	$R_{\theta JA}$		62.5	

Electrical Characteristics (T_c=25°C unless otherwise specified)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-Source breakdown voltage	BV _{DSS}	I _D =250μA, V _{GS} =0	500			V
Gate-Threshold voltage	V _{GS(th)}	I _D =250μA, V _{DS} =5V	2.0		4.0	V
Drain-source leakage current	I _{DSS}	V _{DS} =500V			10	μA
Gate-source leakage	I _{GSS}	V _{DS} =0V, V _{GS} =±30V			±100	nA
Drain-Source on-resistance ④	R _{DS(ON)}	V _{GS} =10V, I _D =2.25A			1.5	Ω
Forward transconductance ④	g _{fs}	V _{DS} =50V, I _D =2.25A		3.87		S
Input capacitance	C _{iSS}	V _{GS} =0V, V _{DS} =25V, f=1MHz		760	900	pF
Output capacitance	C _{oss}			85	100	
Reverse transfer capacitance	C _{rSS}			15	22	
Turn-on delay time	t _{d(on)}	V _{DD} =250V, I _D =4.5A R _G =12Ω		15	40	ns
Rise time	t _r			16	40	
Turn-off delay time	t _{d(off)}			66	140	
Fall time	t _f			22	55	
Total gate charge	Q _g	V _{DS} =400V, V _{GS} =10V, I _D =4.5A		33	43	nC
Gate-source charge	Q _{gs}			4.4		
Gate-drain("Miller")charge	Q _{gd}			16.6		

Source-Drain Diode Ratings and Characteristics

Characteristic	Symbol	Test Condition	Min	Typ	Max	Units
Continuous source current	I _S	Integral reverse pn-diode in the MOSFET			4.5	A
Pulsed-source current ①	I _{SM}				18	
Diode forward voltage ④	V _{SD}	T _J =25°C, V _{GS} =0V, I _S =4.5A			1.4	V
Reverse recovery time	t _{rr}	T _J =25°C, I _F =4.5A di _F /dt=100A/us		285		ns
Reverse recovery charge	Q _{rr}			2.0		uC

Note ;

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② L=30mH, I_{AS}=4.5A, V_{DD}=50V, R_G=27Ω, starting T_J=25°C
- ③ I_{SD} ≤ 4.5A, di/dt ≤ 130A/us, V_{DD} ≤ BV_{DSS}, starting T_J=25°C
- ④ Pulse Test : Pulse Width=250us, Duty cycle ≤ 2%
- ⑤ Essentially independent of operating temperature

Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_{DR} - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $BV_{DSS} - T_J$




Fig. 8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_C$




Fig. 10 Safe operating Area




Fig. 11 Thermal Response




Fig. 12 Gate Charge Test Circuit & Waveform




Fig. 13 Resistive Switching Test Circuit & Waveform




Fig. 14 Unclamped Inductive Switching Test Circuit & Waveform





Fig. 15 Peak Diode Recovery dv/dt Test Circuit & Waveform



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.