

MN1874085

Type	MN1874085		
ROM (x8-bit)	40K		
RAM (x8-bit)	640		
Minimum Instruction Execution Time	2/3 dividing 0.5µs (at 4.5 to 5.5V, 12MHz)		
Interrupts	<ul style="list-style-type: none"> • RESET • External 0 • External 1 • Timer 0 • Timer 1 • Timer 2 • Remote Control • Line 21 • COSD 		
Timer Counter	<p>Timer Counter 0 : 8-bit x 1 Clock Source1/1, 1/4, 1/16, 1/64 of System Clock Interrupt SourceOverflow of Timer Counter 0</p> <p>Timer Counter 1 : 8-bit x 1 Clock Source1/2, 1/16, 1/64, 1/256, 1/512 of System Clock Interrupt SourceOverflow of Timer Counter 1</p> <p>Time Base Counter Clock Source1/4096 of System Clock Interrupt Source1/1, 1/2, 1/4, 1/8 of Timer Counter 2</p> <p>Watchdog</p>		
I/O Pins	I/O	21	• Common use : 3
	Input	1	• Common use : 1
	Output	7	• Nch Open-drain : 7
A/D Inputs	5-bit x 7ch (without S/H)		
PWM	14-bit x 1ch (Repetition Cycle 16µs, at 12MHz), 8-bit x 8ch (Repetition Cycle 32µs, at 12MHz), 7-bit x 1ch (Repetition Cycle 16µs, at 12MHz) (All PWM are 5V ; not connectable to 12V systems)		
Special Ports	Remote Control Reception		
CRTC	Single OSD built-in (Caption OSD : 12 x 26, 256 letters)		
Notes	Remote Control Data Detection Circuit built-in		
Package	SDIP064-P-0750		

Electrical Characteristics

A/D Converter Characteristics


Parameter	Symbol	Condition	Limit			Unit
			min	typ	max	
A/D Conversion Time	TAD	fosc=12MHz	9			µs
Analog Input Voltage	VAD		VSS		VDD	V

(Ta= -20 to +70°C, VDD=5.0V, VSS=0V)

Support Tool

In-Circuit Emulator	PX-ICE1870 / 80 + PX-PRB1879682 (under development)
EPROM built-in Type	Use MN18P79682 in SDIP064-P-0750 package.

Pin Assignment



SDIP064-P-0750