


### Features

- Low Forward Voltage Drop
- Guard Ring Construction for Transient Protection
- Low Capacitance
- Ultra-Small Surface Mount Package
- **Lead Free By Design/RoHS Compliant (Note 1)**
- "Green" Device (Note 2)
- **Qualified to AEC-Q101 Standards for High Reliability**

### Mechanical Data

- Case: DFN1006-2
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: Cathode Dot
- Terminals: Finish — NiPdAu annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Marking Code: LM, Dot Denotes Cathode Side
- Ordering Information: See Last Page
- Weight: 0.001 grams



DFN1006-2			
Dim	Min	Max	Typ
A	0.95	1.075	1.00
B	0.55	0.675	0.60
C	0.45	0.55	0.50
D	0.20	0.30	0.25
G	0.47	0.53	0.50
H	0	0.05	0.03
N	—	—	0.40
R	0.05	0.15	0.10
All Dimensions in mm			

### Maximum Ratings @ T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	30	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	21	V
Maximum (Peak) Forward Current	I <sub>FM</sub>	200	mA
Peak Forward Surge Current 8.3ms Half Sine	I <sub>FSM</sub>	1.0	A
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>STG</sub>	-65 to +125	°C


### Thermal Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Power Dissipation	P <sub>d</sub>	250	mW
Thermal Resistance, Junction to Ambient Air	R <sub>θJA</sub>	400	°C/W


### Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Reverse Breakdown Voltage (Note 3)	V <sub>(BR)R</sub>	30	—	—	V	I <sub>R</sub> = 150μA
Forward Voltage Drop	V <sub>F</sub>	—	—	350 575	mV	I <sub>F</sub> = 20mA I <sub>F</sub> = 200mA
Peak Reverse Current (Note 3)	I <sub>R</sub>	—	—	150 30	μA μA	V <sub>R</sub> = 30V V <sub>R</sub> = 10V
Total Capacitance	C <sub>T</sub>	—	20	—	pF	V <sub>R</sub> = 0V, f = 1.0MHz


- Note:
1. No purposefully added lead.
  2. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
  3. Short duration pulse test used so as to minimize self-heating effect.




$T_A$ , AMBIENT TEMPERATURE (°C)  
Fig. 1 Power Derating Curve



$V_F$ , INSTANTANEOUS FORWARD VOLTAGE (mV)  
Fig. 2 Typical Forward Characteristics



$V_R$ , INSTANTANEOUS REVERSE VOLTAGE (V)  
Fig. 3 Typical Reverse Characteristics



$V_R$ , REVERSE VOLTAGE (V)  
Fig. 4 Typical Total Capacitance vs. Reverse Voltage

**Ordering Information** (Note 4)

Device	Packaging	Shipping
SDM20U30LP-7	DFN1006-2	3000/Tape & Reel

Note: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



LM = Product Type Marking Code, Dot Denotes Cathode Side

**IMPORTANT NOTICE**

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

The products located on our website at [www.diodes.com](http://www.diodes.com) are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.