



Filter Module for ATM Applications

PCA Part Number(s)		EPT7079G			
Electrical Specifications @ 25 °C					
Parameter	Frequency	Specification	XMIT	RCV	Unit
Attenuation	6 KHz		3.0	-----	dB Min.
	4 MHz		0.6	-----	dB Min.
	16 MHz		1.0	-----	dB Min.
	24 MHz		1.8	-----	dB Min.
	36 MHz		10	-----	dB Min.
Return Loss	1-17 MHz		16	-----	dB Min.
	17-25 MHz		9	-----	dB Min.
Common Mode Rejection	5 MHz		30	-----	dB Min.
	20 MHz		30	-----	dB Min.
	200 MHz		20	-----	dB Min.
Crosstalk	5-16 MHz	(Between Channels)	50	-----	Vrms
	24 MHz	(Between Channels)	40	-----	Vrms
Impedance		120			
Notes :					

Schematic



Package



DST7079G Rev.- 5/24/96

QAF-CS07 8/10/94

Unless Otherwise Noted
Dimensions in Inches
Tolerances: Fractional = ± 1/32
.XX = ± .030 .XXX = ± .010



16799 SCHOENBORN ST.
NORTH HILLS, CA 91343

TEL: (818) 892-0761
FAX: (818) 894-5791
WEB: <http://www.pcainc.com>