


Endured surge thick film chip resistor

ESR10 (0805 size : 1 / 4W)

●Features

- 1) Power rating of 1 / 4W (Rated power is more than twice that of MCR series)
- 2) Superior anti surge to MCR series
- 3) Highly reliable chip resistor
Ruthenium oxide dielectric offers superior resistance to the elements.
- 4) ROHM resistors have approved ISO-9001 certification.
Design and specifications are subject to change without notice. Carefully check the specification sheet before using or ordering it.

●Ratings

| Item | Conditions | Specifications | | |
|--------------------------|---|---|--------------------------|------|
| Rated power | <p>Power must be derated according to the power derating curve in Figure 1 when ambient temperature exceeds 70°C.</p>  <p style="text-align: center;">Fig.1</p> | 0.25W (1 / 4W) at 70°C | | |
| Rated voltage | <p>The voltage rating is calculated by the following equation. If the value obtained exceeds the limiting element voltage, the voltage rating is equal to the maximum operating voltage.</p> $E = \sqrt{P \times R}$ <p style="margin-left: 100px;">E: Rated voltage (V) P: Rated power (W) R: Nominal resistance (Ω)</p> | <table border="1" style="width: 100%;"> <tr> <td>Limiting element voltage</td> <td>150V</td> </tr> </table> | Limiting element voltage | 150V |
| Limiting element voltage | 150V | | | |
| Nominal resistance | See Table 1 . | | | |
| Operating temperature | | -55°C to +155°C | | |

Resistors

Table 1

| Resistance tolerance | Resistance range (Ω) | Resistance temperature coefficient (ppm/ $^{\circ}$ C) |
|----------------------|----------------------------------|---|
| D ($\pm 0.5\%$) | $10 \leq R \leq 1M$ (E24,96) | ± 100 |
| J ($\pm 5\%$) | $1 \leq R \leq 10M$ (E24) | ± 200 |


- Before using components in circuits where they will be exposed to transients such as pulse loads (short-duration, high-level loads), be certain to evaluate the component in the mounted state. In addition, the reliability and performance of this component cannot be guaranteed if it is used with a steady state voltage that is greater than its rated voltage.

● Characteristics


| Item | Guaranteed value | Test conditions (JIS C 5201-1) |
|--|--|---|
| | Resistor type | |
| Resistance | J : $\pm 5\%$ D : $\pm 0.5\%$ | JIS C 5201-1 4.5 |
| Variation of resistance with temperature | See Table.1 | JIS C 5201-1 4.8 Measurement : $-55 / +25 / +125^{\circ}$ C |
| Overload | $\pm (2.0\%+0.1\Omega)$ | JIS C 5201-1 4.13 Rated voltage (current) $\times 2.5$, 2s. Maximum overload voltage : 200V |
| Solderability | A new uniform coating of minimum of 95% of the surface being immersed and no soldering damage. | JIS C 5201-1 4.17 Rosin-Ethanol (25%WT) Soldering condition : $235 \pm 5^{\circ}$ C Duration of immersion : 2.0 ± 0.5 s. |
| Resistance to soldering heat | $\pm (1.0\%+0.05\Omega)$ No remarkable abnormality on the appearance. | JIS C 5201-1 4.18 Soldering condition : $260 \pm 5^{\circ}$ C Duration of immersion : 10 ± 1 s. |
| Rapid change of temperature | $\pm (1.0\%+0.05\Omega)$ | JIS C 5201-1 4.19 Test temp. : -55° C to $+125^{\circ}$ C 5cyc |
| Damp heat, steady state | $\pm (3.0\%+0.1\Omega)$ | JIS C 5201-1 4.24 40° C, 93%RH Test time : 1,000h to 1,048h |
| Endurance at 70° C | $\pm (3.0\%+0.1\Omega)$ | JIS C 5201-1 4.25.1 Rated voltage (current), 70° C 1.5h : ON – 0.5h : OFF Test time : 1,000h to 1,048h |
| Endurance | $\pm (3.0\%+0.1\Omega)$ | JIS C 5201-1 4.25.3 155° C Test time : 1,000h to 1,048h |
| Resistance to solvent | $\pm (1.0\%+0.05\Omega)$ | JIS C 5201-1 4.29 $23 \pm 5^{\circ}$ C, Immersion cleaning, 5 ± 0.5 min. Solvent : 2-propanol |
| Bend strength of the end face plating | $\pm (1.0\%+0.05\Omega)$ Without mechanical damage such as breaks. | JIS C 5201-1 4.33 |
| Static electric characteristics | $\pm (5.0\%+0.05\Omega)$ | EIAJ ED-4701 1300 Test method 304 Voltage : 3kv R : $1.5k\Omega$ C : 100pF Apply cycle : 1 time |

Resistors

●External dimensions (Unit : mm)




●Packaging



Resistors

●Part designation



Packaging Specifications Code

| Part No. | Code | Resistance tolerance | | Packaging specifications | Reel | Basic ordering unit(pcs) |
|--------------|------------|----------------------|--------|--------------------------|---------------|--------------------------|
| | | J(±5%) | F(±1%) | | | |
| ESR10 | EZP | ⊙ | ⊙ | Paper tape (4mm Pitch) | φ180mm (7in.) | 5,000 |

Reel (φ180) : JEITA ET-7200B
 ⊙ : Standard product

●Dimensions




Fig.2 Dimensions (length)




Fig.3 Dimensions (width)




Fig.4 Dimensions (thickness)

●Electrical characteristics




Fig.5 Resistance (J class)




Fig.6 Resistance (D class)




Fig.7 Variation of resistance with temperature (J class)

Resistors




Fig.8 Variation of resistance with temperature (D class)




Fig.9 Overload




Fig.10 Solderability




Fig.11 Resistance to soldering heat




Fig.12 Rapid change of temperature




Fig.13 Damp heat, steady state




Fig.14 Endurance at 70°C




Fig.15 Endurance




Fig.16 Component solvent resistance

Resistors




Fig.17 Bend strength of the end face plating




Fig.18 Static electric characteristics

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.