



AO4703

P-Channel Enhancement Mode Field Effect Transistor with Schottky Diode

General Description


The AO4703 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. A Schottky diode is provided to facilitate the implementation of non-synchronous DC-DC converters. *Standard Product AO4703 is Pb-free (meets ROHS & Sony 259 specifications). AO4703L is a Green Product ordering option. AO4703 and AO4703L are electrically identical.*

Features


- V_{DS} (V) = -30V
- I_D = -12A (V_{GS} = -20V)
- $R_{DS(ON)}$ < 14m Ω (V_{GS} = -20V)
- $R_{DS(ON)}$ < 15m Ω (V_{GS} = -10V)

SCHOTTKY

- V_{DS} (V) = 30V, I_F = 3A, V_F =0.5V@1A



SOIC-8



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter | Symbol | MOSFET | Schottky | Units |
|---|----------------|------------------------|------------|------------------|
| Drain-Source Voltage | V_{DS} | -30 | | V |
| Gate-Source Voltage | V_{GS} | ± 25 | | V |
| Continuous Drain Current ^A | I_D | $T_A=25^\circ\text{C}$ | -12 | A |
| | | $T_A=70^\circ\text{C}$ | -10 | |
| Pulsed Drain Current ^B | I_{DM} | -60 | | |
| Schottky reverse voltage | V_{KA} | | 30 | V |
| Continuous Forward Current ^A | I_F | $T_A=25^\circ\text{C}$ | 4.4 | A |
| | | $T_A=70^\circ\text{C}$ | 3.2 | |
| Pulsed Forward Current ^B | I_{FM} | | 30 | |
| Power Dissipation | P_D | $T_A=25^\circ\text{C}$ | 3 | W |
| | | $T_A=70^\circ\text{C}$ | 2.1 | |
| Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | -55 to 150 | $^\circ\text{C}$ |

| Parameter: Thermal Characteristics MOSFET | | Symbol | Typ | Max | Units |
|---|---------------------|-----------------|-----|-----|--------------------|
| Maximum Junction-to-Ambient ^A | $t \leq 10\text{s}$ | $R_{\theta JA}$ | 28 | 40 | $^\circ\text{C/W}$ |
| Maximum Junction-to-Ambient ^A | Steady-State | | 54 | 75 | |
| Maximum Junction-to-Lead ^C | Steady-State | $R_{\theta JL}$ | 21 | 30 | |
| Thermal Characteristics Schottky | | | | | |
| Maximum Junction-to-Ambient ^A | $t \leq 10\text{s}$ | $R_{\theta JA}$ | | 40 | $^\circ\text{C/W}$ |
| Maximum Junction-to-Ambient ^A | Steady-State | | | 75 | |
| Maximum Junction-to-Lead ^C | Steady-State | $R_{\theta JL}$ | | | |

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|-----------------------------|---------------------------------------|---|------|----------|-----------|------------------|
| STATIC PARAMETERS | | | | | | |
| BV_{DSS} | Drain-Source Breakdown Voltage | $I_D=-250\mu\text{A}$, $V_{GS}=0\text{V}$ | -30 | | | V |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS}=-24\text{V}$, $V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$ | | | -1 -5 | μA |
| I_{GSS} | Gate-Body leakage current | $V_{DS}=0\text{V}$, $V_{GS}=\pm 25\text{V}$ | | | ± 100 | nA |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}=V_{GS}$, $I_D=-250\mu\text{A}$ | -1.7 | -2.5 | -3 | V |
| $I_{D(ON)}$ | On state drain current | $V_{GS}=-10\text{V}$, $V_{DS}=-5\text{V}$ | 60 | | | A |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance | $V_{GS}=-10\text{V}$, $I_D=-10\text{A}$ $T_J=125^\circ\text{C}$ | | 12 16 | 15 20 | $\text{m}\Omega$ |
| | | $V_{GS}=-20\text{V}$, $I_D=-10\text{A}$ | | 11 | 14 | $\text{m}\Omega$ |
| | | $V_{GS}=-4.5\text{V}$, $I_D=-10\text{A}$ | | 25 | | $\text{m}\Omega$ |
| g_{FS} | Forward Transconductance | $V_{DS}=-5\text{V}$, $I_D=-10\text{A}$ | | 26 | | S |
| V_{SD} | Diode Forward Voltage | $I_S=-1\text{A}$, $V_{GS}=0\text{V}$ | | -0.72 | -1 | V |
| I_S | Maximum Body-Diode Continuous Current | | | | -4.2 | A |
| DYNAMIC PARAMETERS | | | | | | |
| C_{iss} | Input Capacitance | | | 2076 | | pF |
| C_{oss} | Output Capacitance | $V_{GS}=0\text{V}$, $V_{DS}=-15\text{V}$, $f=1\text{MHz}$ | | 503 | | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 302 | | pF |
| R_g | Gate resistance | $V_{GS}=0\text{V}$, $V_{DS}=0\text{V}$, $f=1\text{MHz}$ | | 2 | | Ω |
| SWITCHING PARAMETERS | | | | | | |
| Q_g | Total Gate Charge | | | 37.2 | | nC |
| Q_{gs} | Gate Source Charge | $V_{GS}=-10\text{V}$, $V_{DS}=-15\text{V}$, $I_D=-12\text{A}$ | | 7 | | nC |
| Q_{gd} | Gate Drain Charge | | | 10.4 | | nC |
| $t_{D(on)}$ | Turn-On Delay Time | | | 12.4 | | ns |
| t_r | Turn-On Rise Time | $V_{GS}=-10\text{V}$, $V_{DS}=-15\text{V}$, $R_L=1.25\Omega$, | | 8.2 | | ns |
| $t_{D(off)}$ | Turn-Off Delay Time | $R_{GEN}=3\Omega$ | | 25.6 | | ns |
| t_f | Turn-Off Fall Time | | | 12 | | ns |
| t_{rr} | Body Diode Reverse Recovery Time | $I_F=-12\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$ | | 33 | | ns |
| Q_{rr} | Body Diode Reverse Recovery Charge | $I_F=-12\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$ | | 23 | | nC |
| SCHOTTKY PARAMETERS | | | | | | |
| V_F | Forward Voltage Drop | $I_F=1.0\text{A}$ | | 0.45 | 0.5 | V |
| I_{rm} | Maximum reverse leakage current | $V_R=30\text{V}$ | | 0.007 | 0.05 | mA |
| | | $V_R=30\text{V}$, $T_J=125^\circ\text{C}$ | | 3.2 | 10 | |
| | | $V_R=30\text{V}$, $T_J=150^\circ\text{C}$ | | 12 | 20 | |
| C_T | Junction Capacitance | $V_R=15\text{V}$ | | 37 | | pF |

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

D: The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

Rev3: August 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

P-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

P-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: SCHOTTKY




Figure 12: Schottky Forward Characteristics




Figure 13: Schottky Capacitance Characteristics




Figure 14: Schottky Forward Drop vs. Junction Temperature




Figure 15: Schottky Leakage current vs. Junction Temperature




Figure 15: Schottky Normalized Maximum Transient Thermal Impedance