

LO568RGB2-80Q-A
Features

70° x 40° Viewing Angle
 5mm Oval Lens
 Pure Green and Pure Blue Color
 White Diffused Lens
 No Stand Offs

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.		Unit
		TPG	TBL	
Forward Current	I _F	25	25	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	100.00	100.00	mW
Operating Temperature	T _{opr}	-40 ~ +95	-40 ~ +95	°C
Storage Temperature	T _{stg}	-40 ~ +100	-40 ~ +100	°C
Soldering Temperature	T _{sol}	260	260	°C
Soldering Time	-	for 3 sec. max	for 3 sec. max	-

Opto-Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min		Typ		Max		Unit
			TPG	TBL	TPG	TBL	TPG	TBL	
Forward Voltage	V _F	I _F =20mA	-	-	3.40	3.40	4.00	4.00	V
Reverse Current	I _R	V _R =5V	-	-	-	-	100	100	μA
Luminous Intensity	I _v	I _F =20mA	-	-	450.00	200.00	-	-	mcd
Viewing Angle	2θ ^{1/2}	-	-	-	70° x 40°	70° x 40°	-	-	deg.
Peak Wavelength	λ _p	I _F =20mA	-	-	522	465	-	-	nm
Dominant Wavelength	λ _d	I _F =20mA	-	-	527	470	-	-	nm
Spectral Line Half Width	Δλ	I _F =20mA	-	-	0	26	-	-	nm

LO568RGB2-80Q-A Graphs

Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725



Web: www.marktechopto.com | Email: info@marktechopto.com

California Sales Office:
950 South Coast Drive, Suite 225
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314