



# Mobile Double Data Rate (DDR) SDRAM

**MT46H16M16LF – 4 Meg x 16 x 4 Banks**

**MT46H8M32LF – 2 Meg x 32 x 4 Banks**

For a complete data sheet, please refer to [www.micron.com/mobilesds](http://www.micron.com/mobilesds).

### Features


- VDD = +1.8V ±0.1V, VDDQ = +1.8V ±0.1V
- Bidirectional data strobe per byte of data (DQS)
- Internal, pipelined double data rate (DDR) architecture; two data accesses per clock cycle
- Differential clock inputs (CK and CK#)
- Commands entered on each positive CK edge
- DQS edge-aligned with data for READs; center-aligned with data for WRITEs
- Four internal banks for concurrent operation
- Data masks (DM) for masking write data—one mask per byte
- Programmable burst lengths: 2, 4, 8, 16 or full page
- Concurrent auto precharge option is supported
- Auto refresh and self refresh modes
- 1.8V LVCMOS compatible inputs
- On-chip temperature sensor to control refresh rate
- Partial array self refresh (PASR)
- Deep power-down (DPD)
- Selectable output drive (DS)
- Clock stop capability

### Options

- VDD/VDDQ
  - 1.8V/1.8V
- Configuration
  - 16 Meg x 16 (4 Meg x 16 x 4 banks) 16M16
  - 8 Meg x 32 (2 Meg x 32 x 4 banks) 8M32
- Plastic Package
  - 60-Ball VFBGA<sup>1</sup> TBD
  - 90-Ball VFBGA<sup>2</sup>
- Timing – Cycle Time
  - 6ns @ CL = 3 -6
  - 7.5ns @ CL = 3 -75
  - 10ns @ CL = 3 -10
- Operating Temperature Range
  - Commercial (0° to +70°C) None
  - Industrial (-40°C to +85°C) IT

### Marking

**Figure 1: 60-Ball VFBGA Assignment**



**Table 1: Configuration Addressing**

Architecture	16 Meg x 16	8 Meg x 32
Configuration	4 Meg x 16 x 4	2 Meg x 32 x 4
Refresh Count	8K	4K
Row Addressing	8K (A0–A12)	4K (A0–A11)
Bank Addressing	4 (BA0, BA1)	4 (BA0, BA1)
Column Addressing	1K (A0–A9)	1K (A0–A9)

Notes: 1. Only available for x16 configuration.  
 2. Only available for x32 configuration.



## 256Mb: 16 Meg x 16, 8 Meg x 32 Mobile DDR SDRAM

---



8000 S. Federal Way, P.O. Box 6, Boise, ID 83707-0006, Tel: 208-368-3900  
prodmktg@micron.com www.micron.com Customer Comment Line: 800-932-4992  
Micron, the M logo, and the Micron logo are trademarks of Micron Technology, Inc.  
All other trademarks are the property of their respective owners.  
**Advance: This data sheet contains initial descriptions of products still under development.**



---

## Revision History

- Original Document, Preview .....03/05