



# RB751V-40

## SURFACE MOUNT SCHOTTKY DIODES

**VOLTAGE** 40 Volts    **CURRENT** 200 mA

### FEATURES

- Extremely Fast Switching Speed
- Very Low  $V_F$  : 0.325V (Typ) at  $I_F = 1\text{mA}$
- Surface mount package ideally suited for automatic insertion
- Pb free product are available : 99% Sn above can meet RoHS environment substance directive request

### MECHANICAL DATA

Case: SOD-323, Plastic


Terminals: Solderable per MIL-STD-750, Method 2026

Approx Weight : 0.008 gram

Marking : P60

SOD-323

Unit: inch (mm)



### ABSOLUTE RATINGS

PARAMETER	Symbol	Value	Units
Maximum Reverse DC Voltage	$V_{RRM}$	40	V
Peak Reverse Voltage	$V_R$	30	V
Maximum Forward Current	$I_F$	0.2	A
Power Dissipation <sup>(1)</sup>	$P_{TOT}$	200	mW
Junction Temperature	$T_J$	-55 to 125	°C
Storage Temperature	$T_{STG}$	-55 to 150	°C

### THERMAL CHARACTERISTICS

PARAMETER	Symbol	Value	Units
Thermal Resistance, Junction to Ambient <sup>(1)</sup>	$R_{\theta JA}$	500	°C/W

1. FR-5 Board = 1.0 x 0.75 x 0.062 in. Minmum Pad Layout






# RB751V-40

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted )

PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Leakage Current	$I_R$	$V_R=30\text{V}$	-	-	0.5	$\mu\text{A}$
Forward Voltage	$V_F$	$I_F=1\text{mA}$	-	-	0.37	V
Total Capacitance	$C_T$	$V_R=1\text{V}, F=1\text{MHz}$	-	3	5	pF


## ELECTRICAL CHARACTERISTICS CURVE





# RB751V-40

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 5K per 7" plastic Reel

## LEGAL STATEMENT

### Copyright PanJit International, Inc 2005

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.