

APAX-5343 APAX-5343E APAX-5001/5002

Power Supply for APAX-5570 Series

Power Supply for APAX Expansion
Modules

1-slot/2-slot Backplane Module

NEW



APAX-5343



Specifications

Input

- **Rated Voltage** 115/230 V_{AC}
- **Voltage Range** 90 ~ 264 V_{AC}
- **Input Current** 1.5 A (at rated load)
- **Input Frequency Range** 47 ~ 63 Hz
- **Inrush Current** 50 A

Output

- **Output Power** 72 watt
- **Rated Voltage** 24 V_{DC}
- **Rated Output Current** 3 A
- **Efficiency** ≥ 88%

Protection

- **Isolation Protection (In/Out)**
- **Over Voltage Protection**
- **Over Load Protection**
- **Short Circuit Protection**


General

- **Dimensions (W x H x D)** 75 x 151 x 115 mm
- **Operating Temperature** 0 ~ 50° C
- **Storage Temperature** -20 ~ 75° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **APAX-5343** Power Supply for APAX-5570 Series
- **APAX-5343E** Power Supply for APAX Expansion Module

NEW



APAX-5001

APAX-5002



Specifications

General

- **Dimensions (W x H x D)** 28 x 151 x 38 mm (APAX-5001)
54 x 151 x 38 mm (APAX-5002)
- **Weight** 70 g (APAX-5001)
120 g (APAX-5002)
- **Mounting** DIN-rail, wall
- **Power Consumption** 0.3 W @ 24 V_{DC} (APAX-5001)
1.3 W @ 24 V_{DC} (APAX-5002)
- **Power Input** 18 ~ 30 V_{DC}
- **Slot Number** 1 (APAX-5001)
2 (APAX-5002)

Environment

- **Operating Temperature** 0 ~ 60° C
- **Storage Temperature** -25 ~ 75° C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **APAX-5001** 1-slot Backplane Module
- **APAX-5002** 2-slot Backplane Module
- **APAX-5343E** Power Supply for APAX Expansion Module