

## Fast Recovery Epitaxial Diode (FRED)

## PSEI 2x161


$$I_{FAVM} = 2x\ 128\ A$$

$$V_{RRM} = 1200\ V$$

$$t_{rr} = 40\ ns$$

Preliminary Data Sheet

$V_{RSM}$ (V)	$V_{RRM}$ (V)	Type
1200	1200	PSEI 2x161/12



Symbol	Test Conditions	Maximum Ratings	
$I_{FRMS}$	$T_{VJ} = T_{VJM}$	270	A
$I_{FAVM}^*$	$T_C = 70\ ^\circ C$ , rectangular, $d=0.5$	128	A
$I_{FSM}$	$T_{VJ} = 45\ ^\circ C$ $t = 10\ ms$ (50 Hz), sine	1200	A
	$V_R = 0$ $t = 8.3\ ms$ (60 Hz), sine	1320	A
	$T_{VJ} = 125\ ^\circ C$ $t = 10\ ms$ (50 Hz), sine	1080	A
	$V_R = 0$ $t = 8.3\ ms$ (60 Hz), sine	1170	A
$\int i^2 dt$	$T_{VJ} = 45\ ^\circ C$ $t = 10\ ms$ (50 Hz), sine	7200	A <sup>2</sup> s
	$V_R = 0$ $t = 8.3\ ms$ (60 Hz), sine	7100	A <sup>2</sup> s
	$T_{VJ} = 125\ ^\circ C$ $t = 10\ ms$ (50 Hz), sine	5800	A <sup>2</sup> s
	$V_R = 0$ $t = 8.3\ ms$ (60 Hz), sine	5700	A <sup>2</sup> s
$T_{VJ}$		-40... + 150	°C
$T_{VJM}$		150	°C
$T_{stg}$		-40... + 125	°C
$V_{ISOL}$	50/60 Hz, RMS $t = 1\ min$	2500	V~
	$I_{ISOL} \leq 1\ mA$ $t = 1\ s$	3600	V~
$M_d$	Mounting torque (M4)	1.5 - 2.0	Nm
		14 - 18	lb.in.
<b>Weight</b>	typ.	24	g

Symbol	Test Conditions	Characteristic Value	
$I_R$	$T_{VJ} = 25\ ^\circ C$ , $V_R = V_{RRM}$	max.	12 mA
	$T_{VJ} = 25\ ^\circ C$ , $V_R = 0.8 \cdot V_{RRM}$	max.	3 mA
	$T_{VJ} = 125\ ^\circ C$ , $V_R = 0.8 \cdot V_{RRM}$	max.	60 mA
$V_F$	$I_F = 200\ A$ , $T_{VJ} = 25\ ^\circ C$	max.	1.90 V
$V_{TO}$	For power-loss calculations only		1.16 V
$r_T$			3 mΩ
$R_{thJC}$	per diode; max.	0.29	K/W
$R_{thCH}$	per diode; typ.	0.2	K/W
$I_{RM}$	$I_F = 100A$ ; $-di_F/dt = 200A/\mu s$ ; $V_R = 100V$ $L \leq 0.05\ mH$ ; $T_{VJ} = 100\ ^\circ C$	typ.	48 A
$t_{rr}$	$I_F = 1A$ ; $-di_F/dt = 400A/\mu s$ ; $V_R = 30V$ ; $T_{VJ} = 25\ ^\circ C$	typ.	40 ns
$d_s$	Creeping distance on surface	11.2	mm
$d_A$	Creeping distance in air	11.2	mm
$a$	Max. allowable acceleration	50	m/s <sup>2</sup>

### Features

- 2 independent FRED in 1 package
- Isolation voltage 3600 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering
- Very short recovery time
- Soft recovery behaviour
- UL registered, E 148688

### Applications

- Antiparallel diode for high frequency switching devices
- Anti saturation diode
- Snubber diode
- Free wheeling diode in converters and motor control circuits
- Rectifiers in switch mode power supplies (SMPS)
- Inductive heating and melting
- Uninterruptible power supplies (UPS)
- Ultrasonic cleaners and welders

### Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability
- Low noise switching
- Small and light weight

Data according to IEC 60747 refer to a single diode unless otherwise stated

\* $I_{FAVM}$  rating includes blocking losses at  $T_{VJM}$ ;  
 $V_R = 0.8 \cdot V_{RRM}$ ; duty cycle  $d = 0.5$

### Package style and outline

Dimensions in mm (1mm = 0.0394")

