

PCM-3110C


1-slot PCMCIA Module

PCM-3112

2-slot PCMCIA Module



PCM-3110C



PCM-3112



Features

- Supports Type I, II, III PCMCIA cards
- 16-bit data bus
- Busy status LED

Features

- Two PCMCIA slots
- Bootable from linear Flash card or ATA Flash, ATA HDD
- 16-bit data bus
- Busy status LED

Specifications

General	
Bus Interface	PC/104 (ISA)
Standard	Compliant with PCMCIA V2.10 and JEIDA 4.1
PC Card Format	Accepts Type I/II/III PCMCIA cards
Data Bus	16-bit
Secondary	Supports (PC/104 or external drive)
PCMCIA	Card drive with PC/104 bus
Drive	1 main PCMCIA slot extended to 2nd slot with extended (TEAC) FDD extended to 3.5" FDD bay
BIOS	Programmable 32 KB SMD boot Flash BIOS
Mechanical and Environmental	
Dimension (L x W)	96 x 90 mm (3.8" x 3.5")
Weight	0.092 kg (0.203 lb)
Temperature	Operating: 0 ~ 60° C (32 ~ 140° F) Storage: -40 ~ 85° C (-40 ~ 185° F)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
Power	
Power Supply Voltage	+5 V, ±5 % tolerance on power supply
Power Consumption	+5 V @ 70 mA (typical)

Packing List

P/N	Description	Quantity
-	User's manual	x 1
PCM-3110C	1-slot PCMCIA Module	x 1

Ordering Information

P/N	Description
PCM-3110C-0000E	PCMCIA Module

Specifications

General	
Bus Interface	PC/104 (ISA)
Standard	Compliant with PCMCIA V2.10 and JEIDA 4.1 spec
PC Card Format	Accepts Type I/II/III PCMCIA cards
Data Bus	16-bit
Secondary	Features 2 x PCMCIA drives
BIOS	Programmable 32 KB SMD-type boot EEPROM BIOS
Mechanical and Environmental	
Dimension (L x W)	96 x 90 mm (3.8" x 3.5")
Weight	0.1 kg (0.22 lb)
Temperature	Operating: 0 ~ 60° C (32 ~ 140° F) Storage: -40 ~ 85° C (-40 ~ 185° F)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
Power	
Power Supply Voltage	+5 V, ±5 % tolerance on power supply
Power Consumption	+5 V @ 70 mA (typical)

Packing List

P/N	Description	Quantity
-	User's manual	x 1
PCM-3112	2-slot PCMCIA Module	x 1

Ordering Information

P/N	Description
PCM-3112-0000E	2-slot PCMCIA module