



BAT750

SCHOTTKY BARRIER DIODE

FEATURES

- Low V_F
- High current capability
- In compliance with EU RoHS 2002/95/EC directives



MECHANICAL DATA

Case : SOT-23, Plastic

Terminals : Solderable per MIL-STD-750, Method 2026

Weight: 0.008gram

Marking : 750



ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Limit	Unit
Collector reverse voltage	V_R	40	V
RMS reverse voltage	$V_{R(RMS)}$	28	V
Forward current (continuous)	I_F	750	mA
Forward voltage@ $I_F=750mA$	V_F	490	mV
Average peak forward current; DC=50%	I_{FAV}	1500	mA
Non repetitive forward current $t_{\leq 100\mu s}$ $t_{\leq 8.3ms}$	I_{FSM}	12 5.5	A
Power dissipation@ $T_A=25^\circ C$	P_{TOT}	350	mW
Typical thermal resistance, junction to ambient air	$R_{\theta JA}$	286	$^\circ C/W$
Storage temperature range	T_{STG}	-55 to + 150	$^\circ C$
Junction temperature	T_J	125	$^\circ C$

PAN JIT RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN,FUNCTIONS AND RELIABILITY WITHOUT NOTICE



BAT750


ELECTRICAL CHARACTERISTICS (@T_A=25°C unless otherwise stated)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse breakdown voltage	V _{(BR)R}	I _R =300μA	40	60	-	V
Forward voltage(Note 1)	V _F	I _F =50mA	-	250	280	mV
		I _F =100mA	-	270	310	
		I _F =250mA	-	310	350	
		I _F =500mA	-	350	420	
		I _F =750mA	-	390	490	
		I _F =1000mA	-	420	540	
Reverse current	I _R	V _R =30V	-	50	100	μA
Off state junction capacitance	C _J	V _R =25V, f=1.0MHz	-	18	-	pF

Note : 1.Measured under pulsed conditions. Pulse width = 300μ duty cycle < 2%



MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.