



# High Performance BGA Cooling Solutions w/ maxiGRIP™ Attachment


#### ATS PART # ATS-53425D-C2-R0

#### **Features & Benefits**

- » High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- » maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- » Designed specifically for BGAs and other surface mount packages
- » Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock Testing and Unpackaged Drop Testing standards
- » Comes preassembled with high performance thermal interface material







\*Image above is for illustration purposes only.

### **Thermal Performance**

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)	
200	1.0	8.4	3.6	
300	1.5	5.9		
400	2.0	4.9		
500	2.5	4.3		
600	3.0	3.9		
700	3.5	3.6		
800	4.0	3.4		

## **Product Details**

DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	INTERFACE MATERIAL	FINISH
42.5 mm	42.5 mm	9.5 mm	42.5 mm	SAINT-GOBAIN C675	BLACK-ANODIZED

#### NOTES:

- 1) Dimension C = heat sink height from bottom of the base to the top of the fin field.
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- 4) ATS reserves the right to update or change its products without notice to improve the design or performance.
- 5) Optional maxiGRIP™ Installation/Removal Tool Set P/N: MGT425
- 6) Contact ATS to learn about custom options available.



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).