



PCB LAYOUT (BOTTOM VIEW)

Materials and Finish

Material-PBT Thermoplastic
 UL94V-0 Rated
 Color: black
 Contact-Brass, Tin Plated

Mechanical Characteristics

Insertion Force
 0.5kg - 4.5kg
 Withdrawal Force
 0.5kg - 4.5kg
 Durability
 5000 cycles

Electrical Characteristics

Rated Current: 2.0 AMP DC
 Rated Voltage: 24.0 V DC
 Insulation Resistance
 100 Megohms min. at 500V DC
 Contact Resistance
 Before Test: 50 Milliohms max.
 After Test: 100 Milliohms max.
 Dielectric Withstanding Voltage
 500V AC for 1 minute
 Operating Temperature
 -25°C to 85°C

RoHS COMPLIANT
 EU Directive 2002/95/EC

Tolerances

X.X ± 0.25
 X.XX ± 0.15
 Unless Stated
 Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	8/4/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	07/18/05

KCDX-8S-N2

Circular DIN, 8 position, RoHS Compliant

Non-shielded, 5mm spacing

