

MATERIAL


stem-polypropylene, white
nut-polypropylene, white
float-polypropylene, white
seal to side wall of reservoir-Viton, black
Schaft-Polypropylen, weiss
Mutter-polypropylen-weiss
Schwimmer-Polypropylen weiss
Montagedichtung zur Behälterseitenwand-Viton, schwarz

CABLE

round cable LIYY 2x0,14 mm², grey
colour of wires: white and braun
Rundkabel LIYY 2x0,14 mm², grau
Aderfarben: weiss und braun

MARKING

MEDER-label,
Production code EN60062/
factory code, Part number
MEDER-Logo
Produktionscode EN60062/
Fertigungsstätte,
Artikelnummer



tolerances according to DIN ISO 2768 m



Europe: +49 / 7731 8399 0 | Email: info@meder.com
 USA: +1 / 508 295 0771 | Email: salesusa@meder.com
 Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
9534196154
 Item:
LS03/DK-1A66-PP-500W
LS03/DK-PP-BV96154

Products for tomorrow...

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			180	V
Carry current	DC or Peak AC			1,25	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive Sensor deactivated			290	mOhm
Housing material		PP			
Case colour		white			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C
Safety class	DIN EN 60529	IP68			

Cable specification	Conditions	Min	Typ	Max	Unit
Cable type		round cable			
Cable material		PVC			
Cross section		0,14 sq-mm			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a resistor is recommended.			
Tightening torque				1	Nm

Modifications in the sense of technical progress are reserved

Designed at: 20.07.09 Designed by: WKOVACS
 Last Change at: 13.10.09 Last Change by: WKOVACS

Approval at: 21.07.09 Approval by: DKUECHLER
 Approval at: 26.10.09 Approval by: HWEDELE

Version: 03