







- Optimized for Leading Transceiver I.C.'s
- Operating Temperature : -25°C to +85°C
- Add "-RC" after part number for RoHS Compliant
- 12 Pin Surface Mount Package
- 1500 Vrms Isolation

Electrical Parameters @ 25°C


Turns Ratio (± 3%)		OCL (mH Min.)	Cw/w (pF Max.)	LL (µH Max.)	DCR (Max.)
1CT:1.41CT	1CT:1CT	20	130	5.0	2.8
Pins 1-3:12-10	Pins 4-6:9-7	Pins 1-3, 4-6		Pins 1-3, 4-6	Pins 1-3, 4-6

• Minimum OCL @ -25°C : 13 mH Min. •

Package



Schematics



Notes :	EPR1064G	EPR1064G-RC
1. Lead Finish	SnPb	Matte Tin
2. Peak Temperature Rating	225°C	260°C
3. Moisture Sensitive Levels	MSL = 3 (168 Hours, 30°C/60%RH)	MSL = 4 (72 Hours, 30°C/60%RH)
4. Weight	TBD grams	TBD grams
5. Packaging Information (*Add "TR" to end of part number when placing order)	(Tube)	TBD pieces/tube
	(Tape & Reel)	TBD pieces/13" reel (*EPR1064G-TR)
		TBD pieces/13" reel (*EPR1064G-RCTR)

Unless Otherwise Specified Dimensions are in Inches /mm ± .010 / .25