



Straight Plug, Class PG




CGL06PG-B
with bayonet coupling

CGL06PG-B designates a straight plug for the use of heat shrink boots or PG terminations. It mates with receptacle **CGL02A-B**.




Part No.	A	E	L	W
Socket insert	max	max	max	PG Thread
CGL06PG18-11S-C1L-B*	36,5 (1.437)	18 (.709)	70 (2.756)	PG21
CGL06PG18-11S-E1-B*	36,5 (1.437)	32 (1.260)	70 (2.756)	PG21
CGL06PG20-3S-B1-B*	39,9 (1.571)	32 (1.260)	70 (2.756)	PG21
CGL06PG20-17S-C1-B*	39,9 (1.571)	32 (1.260)	70 (2.756)	PG21
CGL06PG22-22S-D1L-B*	43,1 (1.697)	32 (3.228)	70 (2.756)	PG21
CGL06PG28A16S-B1L-B*	53,4 (2.102)	50 (1.969)	77 (3.031)	PG36
CGL06A36A35S-D1L-B*	53,4 (2.102)	60 (2.362)	99 (3.898)	PG42



CGL06PG
with threaded coupling

CGL06PG designates a straight plug for the use of heat shrink boots or PG terminations. It mates with receptacle **CGL02A**.



Part No.	A	C	E	L	W
Socket insert	max	Thread		max	PG Thread
CGL06PG10SL-3S-C1L-*	22,8 (.898)	5/4-24NEF-F2B	18 (.707)	60 (2.362)	PG9
CGL06PG18-10S-D1L-*	36,5 (1.437)	1-1/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG18-11S-C1L-*	36,5 (1.437)	1-1/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG18-11S-E1-*	36,5 (1.437)	1-1/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG20-3S-B1-*	39,9 (1.571)	1-1/4-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG20-15S-E1-*	39,9 (1.571)	1-1/4-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG20-17S-C1-*	39,9 (1.571)	1-1/4-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG22-16S-D1-*	43,1 (1.697)	1-3/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG22-22S-D1L-*	43,1 (1.697)	1-3/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG22-23S-F1L-*	43,1 (1.697)	1-3/8-18NEF-2B	32 (1.260)	70 (2.756)	PG21
CGL06PG24-10S-G1L-*	46,6 (1.835)	1-1/2-18NEF-2B	40 (1.575)	72 (2.835)	PG29
CGL06PG24-11S-G1-*	46,6 (1.835)	1-1/2-18NEF-2B	40 (1.575)	72 (2.835)	PG29
CGL06PG28A16S-B1L-*	53,4 (2.102)	1-3/4-18NS-2B	50 (1.969)	77 (3.031)	PG36