


Ultrasonic proximity sensors

UNDK 20 (Sd = 1000 mm)

sample drawing



general data

scanning range sd	100 ... 1000 mm
scanning range far limit Sde	100 ... 1000 mm
hysteresis typ.	4 % Sde
repeat accuracy	< 0,5 mm
temperature drift	< 0,18 % Sde/K
response time ton	< 50 ms
release time toff	< 50 ms
alignment aid	target indication flashing
sonic frequency	240 kHz
output indicator	LED green
adjustment	Teach-in

electrical data

voltage supply range +Vs	12 ... 30 VDC
current consumption max.	35 mA
output current	< 200 mA
voltage drop Vd	< 2 VDC
residual ripple	< 10 % Vs
short circuit protection	yes
reverse polarity protection	yes

mechanical data

width / diameter	20 mm
height / length	42 mm
depth	15 mm
connection types	connector M8
type	rectangular
housing material	polyester

ambient conditions

operating temperature	-10 ... +60 °C
protection class	IP 67

sample picture



Ultrasonic proximity sensors**UNDK 20 (Sd = 1000 mm)**

order reference	output circuit
UNDK 20N6903/S35A	NPN make function (NO)
UNDK 20N7903/S35A	NPN break function (NC)
UNDK 20P6903/S35A	PNP make function (NO)
UNDK 20P7903/S35A	PNP break function (NC)