

The LS3N170 is an enhancement mode N-Channel Mosfet

The LS3N170 is an enhancement mode N-Channel Mosfet designed for use as a General Purpose amplifier or switch

The hermetically sealed TO-72 package is well suited for high reliability and harsh environment applications.

(See Packaging Information).

LS3N170 Features:

- Low ON Resistance
- Low Capacitance
- High Gain
- High Gate Breakdown Voltage
- Low Threshold Voltage

FEATURES

DIRECT REPLACEMENT FOR INTERSIL LS3N170

LOW DRAIN TO SOURCE RESISTANCE $r_{DS(on)} \leq 200\Omega$

FAST SWITCHING $t_{d(on)} \leq 3.0ns$

ABSOLUTE MAXIMUM RATINGS (Note 1)
@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature -65°C to +150°C

Operating Junction Temperature -55°C to +135°C

Maximum Power Dissipation

Continuous Power Dissipation 300mW

MAXIMUM CURRENT

Drain to Source 30mA

MAXIMUM VOLTAGES

Drain to Gate $\pm 35V$

Drain to Source 25V

Peak Gate to Source $\pm 35V$

LS3N170 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
BV_{DSS}	Drain to Source Breakdown Voltage	25	--	--	V	$I_D = 10\mu A, V_{GS} = 0V$
$V_{DS(on)}$	Drain to Source "On" Voltage	--	--	2.0		$I_D = 10mA, V_{GS} = 10V$
$V_{GS(th)}$	Gate to Source Threshold Voltage	1.0	--	2.0		$V_{DS} = 10V, I_D = 10\mu A$
I_{GSS}	Gate Leakage Current	--	--	10	pA	$V_{GS} = -35V, V_{DS} = 0V$
I_{DSS}	Drain Leakage Current "Off"	--	--	10	nA	$V_{GS} = 10V, V_{DS} = 10V$
$I_{D(on)}$	Drain Current "On"	10	--	--	mA	$V_{GS} = 10V, V_{DS} = 10V$
g_{fs}	Forward Transconductance	1000	--	--	μS	$V_{DS} = 10V, I_D = 2mA, f = 1kHz$
$r_{DS(on)}$	Drain to Source "On" Resistance	--	--	200	Ω	$V_{GS} = 10V, I_D = 0A, f = 1kHz$
C_{rss}	Reverse Transfer Capacitance	--	--	1.3	pF	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$
C_{iss}	Input Capacitance	--	--	5		$V_{DS} = 10V, V_{GS} = 0V, f = 1MHz$
C_{db}	Drain to Body Capacitance	--	--	5.0		$V_{DB} = 10V, f = 1MHz$

SWITCHING CHARACTERISTICS

SYMBOL	CHARACTERISTIC	MAX	UNITS	CONDITIONS
$t_{d(on)}$	Turn On Delay Time	3	ns	$V_{DD} = 10V, I_{D(on)} = 10mA, V_{GS(on)} = 10V, V_{GS(off)} = 0V, R_G = 50\Omega$
t_r	Turn On Rise Time	10		
$t_{d(off)}$	Turn Off Delay Time	3		
t_f	Turn Off Fall Time	15		

Note 1 - Absolute maximum ratings are limiting values above which LS3N170 serviceability may be impaired.


Micross Components Europe

Available Packages:

LS3N170 in TO-72
LS3N170 in bare die.

Please contact Micross for full package and die dimensions

TO-72 (Bottom View)



* Body tied to case



Tel: +44 1603 788967

Email: chipcomponents@micross.com

Web: <http://www.micross.com/distribution>

Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.