


**2SD826****20V/5A Switching Applications****Features**

- Low saturation voltage.
- High h_{FE} .
- Large current capacity.

Package Dimensions

unit:mm

2009A

**Specifications****Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$**

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V_{CB0}		60	V
Collector-to-Emitter Voltage	V_{CE0}		20	V
Emitter-to-Base Voltage	V_{EBO}		6	V
Collector Current	I_C		5	A
Collector Current (Pulse)	I_{CP}	100ms, 1 pulse	8	A
Collector Dissipation	P_C		1.0	W
		$T_c=25^\circ\text{C}$	10	W
Junction Temperature	T_J		150	$^\circ\text{C}$
Storage Temperature	T_{stg}		-55 to +150	$^\circ\text{C}$

Electrical Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I_{CBO}	$V_{CB}=50\text{V}, I_E=0$			1.0	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=5\text{V}, I_C=0$			1.0	μA
DC Current Gain	h_{FE1}	$V_{CE}=2\text{V}, I_C=0.5\text{A}$	120*		560*	
	h_{FE2}	$V_{CE}=2\text{V}, I_C=3\text{A (Pulse)}$	95			
Gain-Bandwidth Product	f_T	$V_{CE}=10\text{V}, I_C=50\text{mA}$		120		MHz
Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, f=1\text{MHz}$		45		pF

* : The 2SD826 is classified by 0.5A h_{FE} as follows.

Continued on next page.

120	E	200	160	F	320	280	G	560
-----	---	-----	-----	---	-----	-----	---	-----

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

SANYO Electric Co., Ltd. Semiconductor Business Headquarters

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN






21599TH (KT)/5277KI/3115KI/5244KI, TS No.538-1/5

2SD826






Continued from preceding page.

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=3A, I_B=60mA$ (Pulse)			0.5	V
Base-to-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=3A, I_B=60mA$ (Pulse)			1.5	V
Turn-ON Time	t_{on}	See specified test circuit.		30		ns
Storage Time	t_{stg}	See specified test circuit.		300		ns
Fall Time	t_f	See specified test circuit.		40		ns


Switching Time Test Circuit



2SD826






Sample Application Circuit 1 : Electronic flash set




	E[V]	r[Ω]	MC[μF]	C1[μF]	R[kΩ]	C2[μF]	Tr	P	F	S	Core
NiCd ×2	2.7	0.15	to 500	100	2.2	0.01	2SD826 FG	0.55ø× 10 ³ / ₄ T	0.23ø× 12 ³ / ₄ T	0.07ø× 1350T	EE13
Alkali or manganese ×4	6.0	1.2	500 to 900	100	4.7	0.015	2SD826 EFG	0.6ø× 22 ³ / ₄ T	0.23ø× 20 ³ / ₄ T	0.08ø× 1390T	EE16
NiCd ×4	5.4	0.3	500 to 1200	100	33	0.0068	2SD826 EF×2	0.6ø× 22 ³ / ₄ T	0.23ø× 20 ³ / ₄ T	0.08ø× 1390T	EE16

2SD826




Sample Application Circuit 2 : High-grade electronic flash set



DC/DC CONVERTER TRANS

- P: 0.6 ϕ 22 ³/₄T
- F: 0.23 ϕ 20 ³/₄T
- S: 0.08 ϕ 1390T
- CORE: EE16

Unit (resistance : Ω , capacitance : F)



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of February, 1999. Specifications and information herein are subject to change without notice.