



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SSR05C60 Series

5 AMP / 600V SILICON CARBIDE SCHOTTKY RECTIFIER

DESIGNER'S DATA SHEET

Part Number / Ordering Information ^{1/}

SSR05C

Screening: = Not Screened
 TX = TX Level
 TXV = TXV Level
 S = S Level

Package: D1 = TO-252 (D-Pack)
 G = Cerpack
 S.5 = SMD.5
 S.22 = SMD.22

Voltage 50 = 500 V
 60 = 600 V

- Features:**
- 600V Silicon Carbide Schottky Rectifier
 - New Semiconductor Material
 - Switching Behavior Benchmark
 - No Reverse Recovery
 - No Forward Recovery
 - No Switching Time Change Over Temperature
 - Hermetic Packages Available

Maximum Ratings		Symbol	Value	Units
Peak Repetitive Reverse and Peak Surge Reverse Voltage	SSR05C50	V_{RRM}	500	Volts
	SSR05C60	V_{RSM}	600	
Average Rectified Forward Current (Resistive Load, 60 Hz Sine Wave)		I_o	5	Amps
Non Repetitive Peak Surge Current (8.3 ms Pulse, Half Sine Wave)		I_{FSM}	20	Amps
I^2t Value		I^2t	0.78	A^2s
Power Dissipation		P_D	36.5	Watts
Operating & Storage Temperature		Top & Tstg	-55 to +175	$^{\circ}C$
Maximum Thermal Resistance Junction to Case		$R_{\theta JC}$	4.1	$^{\circ}C/W$

<p>TO-252 (D1)</p>	<p>Cerpack (G)</p>	<p>SMD.5 (S.5)</p>	<p>SMD.22 (S.22)</p>
---------------------------	---------------------------	---------------------------	-----------------------------



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SSR05C60 Series

Electrical Characteristic	Symbol	Min	Typ	Max	Units
Instantaneous Forward Voltage Drop ($I_F = 5A, T_J = 25^\circ C, 300 \mu sec$ pulse)	V_{F1}	—	1.7	2.0	Volts
Instantaneous Forward Voltage Drop ($I_F = 5A, T_J = 150^\circ C, 300 \mu sec$ pulse)	V_{F2}	—	2.0	2.7	Volts
Reverse Leakage Current ($V_R = \text{Rated } V_R, T_J = 25^\circ C, 300 \mu sec$ pulse min)	I_{R1}	—	15	200	μA
Reverse Leakage Current ($V_R = \text{Rated } V_R, T_J = 100^\circ C, 300 \mu sec$ pulse min)	I_{R2}	—	40	1000	μA
Junction Capacitance ($V_R = 10 V_{DC}, T_C = 25^\circ C, f = 1MHz$)	C_J	—	50	—	pF
Total Capacitive Charge ($V_R = 400V, I_F = 5A, di/dt = 200A/\mu s, T_J = 150^\circ C$)	Q_C	—	13	—	nC

NOTES:
 1/ For Ordering Information, Price, and Availability Contact Factory.
 2/ For Package Outlines Contact Factory.
 3/ All Electrical Characteristics @25°C Unless Otherwise Specified.

Available Part Numbers:
 SSR05C50D1 SSR05C50G SSR05C50S.5
 SSR05C50S.22
 SSR05C60D1 SSR05C60G SSR05C60S.5
 SSR05C60S.22

PIN ASSIGNMENT				
Package	Pin 1	Pin 2	Pin 3	Tab
TO-252 (D1)	N/C	Cathode	Anode	Cathode
Cerpack (G)	Anode	Anode	N/A	Cathode
SMD.5 (S.5)	Cathode	Anode	Anode	N/A
SMD.22 (S.22)	Cathode	Anode	Anode	N/A

NOTE: All specifications are subject to change without notification. SC'D's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RS0016H

DOC