



Ideal for OEM light-fixture manufacturers, Molex LED Array Holders simplify the installation process for next-generation, energy-efficient Citizen CLL010 through CLL050 arrays and reduce installation time with compression contacts that eliminate hand soldering

LED technology has been proven to reduce the amount of energy consumed and is becoming a more reliable, efficient and user-friendly way for accommodating general illumination requirements. Using unmatched interconnect technology, Molex provides a solderless solution to mounting LED arrays into OEM designs.

LED array holders simplify the LED installation process by eliminating the need for hand or SMT soldering and expensive SMT equipment. The holders allow customers to install LED arrays quickly into fixtures, enable field replacements and facilitate upgrades to current applications.

For additional information visit: www.molex.com/link/ledholdercitizen.html

For information about additional Solid State Lighting (SSL) that complements Citizen and other array products visit: www.molex.com/industry/solidstatelighting.html

Features and Benefits

| | |
|--|---|
| Flexible one- and two-piece versions available (CLL010 through CLL050) | Provides design flexibility for multiple arrays. Accommodates the installation of five LED arrays using the same components |
| Compression contacts deliver power to array | Ensure stable connection in high-ambient temperatures. Simplifies the LED installation process by eliminating hand soldering or expensive Surface Mount Technology (SMT) equipment. Reduces installation time |
| Double-ended wire-trap terminal to attach power source (One-piece design only) | Allows for wiring serial or parallel LED sequences, ensuring ease of array assembly |
| Screw-mount attachment method for securing array to heat sink | Provides voltage isolation between LED and heat sink with external mounting holes |
| Releasable wire-trap for rework or replacement | Allows for field serviceability |
| High-temperature thermoplastic housing | Supports high heat-generating environments |
| Wire-trap cap optional (two-piece design only) | Minimizes risk of electric arcs between metal optic and power source |


LED Array Holders for Citizen* For CLL010, CLL020, CLL030, CLL040 and CLL050 Arrays

New Releases

- 180414** One-Piece Holder for CLL020 and CLL030
- 180416** One-Piece Holder for CLL040

Previously Released

- 180412** One-Piece Holder for CLL010
- 180414** Two-Piece Holder for CLL020 and CLL030
- 180416** Two-Piece Holder



LED Array Holder for Citizen Arrays (One-piece option shown as reference)



LED Array Holder for Citizen Arrays (Two-piece option shown as reference)

*Citizen is a registered trademark of Citizen Electronics Co., Ltd.

Specifications

Reference Information

Packaging: Tray
 UL File No.: Pending
 CSA File No.: Pending
 Designed In: Millimeters
 RoHS: Yes
 REACH SVHC: Contains SVHC: No

Electrical

Voltage (max.): 600V DC
 Current (max.):
 2.5A continuous; 3.5A max.
 Contact Resistance:
 20 milliohms max.
 Dielectric Withstanding Voltage:
 300V DC
 Insulation Resistance:
 5000 Megohms min.

Mechanical











Wire Insertion Force:
 5N (1.12 lbf) max.
 Wire Pull Out Force:
 20N (5.62 lbf) max.
 Durability (min.): 5 Cycles

Physical

Housing:
 Contact:
 Copper (Cu), Nickel (Ni) and Gold (Au)
 Plating:
 Contact Area — Gold (Au)
 Underplating — Nickel (Ni)

**LED Array Holders
 for Citizen*
 For CLL010,
 CLL020, CLL030,
 CLL040 and CLL050
 Arrays**

Additional Product Features

| Citizen Arrays | Molex One-Piece Holders | | Molex Two-Piece Holders (Wire Trap Cap available for Two-Piece Design only) | |
|---|---|--------------------|--|--------------------|
| | Series | Assembled Diameter | Series | Assembled Diameter |
|  CLL010 |  180412 | 32.45mm x 25.00mm | Not Available | |
|  CLL020 |  180414 | 26.00mm x 34.85mm |  180414 | 36.30mm x 29.27mm |
|  CLL030 | | 26.00mm x 40.50mm | | 41.80mm x 34.77mm |
|  CLL040 |  18416 | 33.75mm x 46.25mm |  180416 | 47.55mm x 42.12mm |
|  CLL050 | Not Available | | | 57.55mm x 52.12mm |

Citizen CLL Arrays (sold separately, available from Citizen Electronics, Co., Ltd <http://ce.citizen.co.jp/e/>)
 Citizen CLL Arrays are offered in several different lumen output levels and various color temperatures

*Citizen is a registered trademark of Citizen Electronics Co., Ltd.

Applications

All general illumination applications

- Downlighting
- Track
- Pendants
- Linear

Area Lighting

- Roadways
- Parking Lots
- Wall Packs



**LED Array Holders
for Citizen*
For CLL010,
CLL020, CLL030,
CLL040 and CLL050
Arrays**



Recessed downlighting in residential and commercial buildings

Ordering Information

| Order No. | Design Type | Citizen Array |
|-------------|-------------|------------------|
| 180412-0001 | One-Piece | CLL010 |
| 180414-0001 | Two-Piece | CLL020 CLL030 |
| 180414-0102 | One-Piece | CLL020 |
| 180414-0103 | | CLL030 |
| 180416-0001 | Two-Piece | CLL040 CLL050 |
| 180416-0104 | One-Piece | CLL040 |

*Citizen is a registered trademark of Citizen Electronics Co., Ltd.