



50 Ohm 0.5 Watts Brass TNC Male RF Load Up To 1,000 MHz

TECHNICAL DATA SHEET PE6011-50

50 Ohm 0.5 Watts Brass TNC Male RF Load Up To 1,000 MHz

Configuration

Connector TNC Male

Electrical Specifications

Frequency Range, MHz DC to 1,000
Impedance, Ohms 50
Maximum Input Power, Watts +27

Mechanical Specifications

Temperature

Size

Length, in [mm] 1.17 [29.72]
Width/Dia., in [mm] 0.59 [14.99]

Connector

Type TNC Male
Inner Conductor Material and Plating Gold
Outer Conductor Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: <http://www.pasternack.com/0.5-watts-tnc-male-rf-load-up-to-1-ghz-pe6011-50-p.aspx>

50 Ohm 0.5 Watts Brass TNC Male RF Load Up To 1,000 MHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE6011-50 CAD Drawing

50 Ohm 0.5 Watts Brass TNC Male RF Load Up To 1,000 MHz

