

Part Number: C1701

Revision Level: 11/19/2012

4C 12AWG 65/30BC PP, PVC**COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 12 AWG 65/30 BC
Insulation: .009" Wall, Polypropylene (PP)
Cable Core: 4C @ 4.00" LHL
Jacket: .030" Polyvinyl Chloride (PVC)
Print Legend:

**CAROL® -- C1701 -- 4C 12AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8
CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA
(Date code) (Seq Footage)**

DIAMETERS

.088" nom
.106" nom
.257" nom
.317" nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +80°C
Suggested Working Voltage: 600V Max
Conductor DCR: 1.61 Ohms/M' @ 20°C (nom)
Mutual Capacitance: 25.1 pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
Date: _____