

Part Number: C1803

Revision Level: 11/19/2012

4C 14 AWG (105/34) OFHC BC PP, PVC
COMMAND® SERIES
A. CONSTRUCTION

Conductor:	14 AWG 105/34 BC	<u>DIAMETERS</u>
Insulation:	.009" Wall, Polypropylene (PP)	.074" nom
Cable Core:	4C @ 3.50" LHL	.092" nom
Jacket:	.030" Polyvinyl Chloride (PVC)	.223" nom
Print Legend:	CAROL ® -- C1803 -- COMMAND OFHC HD 14AWG 4C ROHS -- 75C E60233-8 (UL) CL3 -- LL69381 CSA AWM I/II A/B 80C 600V FT4 -- MADE IN USA (Date code) (Seq Footage)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	2.62 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	23.8pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____