

Part Number Designator

PE-B159-ZZ
REPLACE ZZ WITH JACKET COLOR

BK	BLACK
BL	BLUE
GR	GREEN
RD	RED
WH	WHITE
YW	YELLOW



IMPEDANCE: 75 OHMS
 INNER CONDUCTOR DIAMETER: .023"
 INNER CONDUCTOR MATERIAL: BARE COPPER
 DIELECTRIC DIAMETER: .102"
 DIELECTRIC MATERIAL: FOAM HIGH DENSITY POLYETHYLENE
 NUMBER OF SHIELDS: 2
 SHIELD MATERIALS: TAPE-ALUMINUM FOIL-POLYESTER
 BRAID-TINNED COPPER
 OUTER DIAMETER: .159"
 JACKET MATERIAL: POLYVINYL CHLORIDE
 NOMINAL CAPACITANCE (pf/ft): 16.3
 OPERATING TEMPERATURE: -30° TO +75° C
 MAX OPERATING VOLTAGE (VOLTS RMS): 300

NOMINAL ATTENUATION (PER 100 FEET)

500 MHz	7.5dB
1 GHz	10.5dB
3 GHz	18.5dB
5 GHz	23.5dB



PASTERNAK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE		DES.			
PE-B159-ZZ		MINI-RG59 PRECISION VIDEO COAXIAL CABLE			
REV. -	FSCM NO. 53919	CAD FILE	051309	SCALE	N/A
		SIZE	A	127	

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES.