

VI TELEFILTER

Filter specification

TFS 76B

1/5

Measurement condition

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	56 Ω 28,5 pF	
Output:	50 Ω 0 pF	

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 76B is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 1 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 76,8 MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

Data		typ. value		tolerance / limit	
Insertion loss (reference level)	a_e	20,8	dB	max.	23 dB
Nominal frequency	f_N	-			76,8 MHz
Centre frequency	f_c	76,8	MHz	±	75 kHz
Passband	PB	-		f_c ±	3,2 MHz
Pass band ripple		-			-
Relative attenuation	a_{rel}				
f_c	... f_c ±	3,20	MHz	0,35	dB
f_c ±	3,20 MHz ... f_c ±	3,50	MHz	-	max. 1 dB
f_c ±	3,65 MHz ... f_c ±	4,85	MHz	-	min. 1 dB
f_c ±	4,85 MHz ... f_c ±	5,00	MHz	61	dB
f_c -	71,8 MHz ... f_c -	5,00	MHz	65	dB
f_c +	5,00 MHz ... f_c +	123,20	MHz	55	dB
Average group delay within PB		1,9	µs	max.	3 µs
Group delay ripple within PB		60	ns	max.	100 ns
Deviation from linear phase within PB		0,2	°rms	max.	2 °rms
Operating temperature range	OTR	-		-	0 °C ... + 70 °C
Storage temperature range		-		-	- 20 °C ... + 80 °C
Temperature coefficient of frequency	TC_f **	- 76	ppm/K		-

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

**) $\Delta f_c(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_0) \times f_{CAT}(\text{MHz})$.



Generated:

Checked / Approved:

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com


VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Filter characteristic



Construction and pin connection


(All dimensions in mm)



- 1 Input
- 2 Ground
- 9 Output RF Return
- 10 Output
- 11 Ground
- 18 Input RF Return

Date code: Year + week
 U 2006
 V 2007
 W 2008
 ...

50 Ω Test circuit



Tele Filter GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:


1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

This filter is RoHS compliant (2002/95/EG, 2005/618/EG)

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile



VI TELEFILTER**Filter specification****TFS 76B****5/5****History**

Version	Reason of Changes	Name	Date
1.0	- generate specification according to customer requirements	Pfeiffer	10.04.2003
1.1	- Add filter characteristic and change stability characteristics	Strehl	14.11.2006

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.