

1SR124-100A ~ 1SR124-400A

PRV : 100 - 400 Volts

Io : 1.0 Ampere

FEATURES :


- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * Fast switching for high efficiency
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : DO-41 Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.339 gram

FAST RECOVERY RECTIFIER DIODES

DO - 41



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

RATING	SYMBOL	1SR124 -100	1SR124 -200	1SR124 -400	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	100	200	400	V
Maximum RMS Voltage	V _{RMS}	70	140	280	V
Maximum DC Blocking Voltage	V _{DC}	100	200	400	V
Maximum Average Forward Current 0.375"(9.5mm) Lead Length Ta = 55 °C	I _{F(AV)}	1.0			A
Maximum Peak Forward Surge Current, 8.3ms Single half sine wave Superimposed on rated load (JEDEC Method)	I _{FSM}	35			A
Maximum Peak Forward Voltage at I _F = 1.0 Amp.	V _F	1.3			V
Maximum DC Reverse Current Ta = 25 °C	I _R	5			μA
at Rated DC Blocking Voltage Ta = 100 °C	I _{R(H)}	50			μA
Maximum Reverse Recovery Time (Note 1)	T _{rr}	250			ns
Typical Junction Capacitance (Note 2)	C _J	50			pf
Junction Temperature Range	T _J	- 65 to + 150			°C
Storage Temperature Range	T _{STG}	- 65 to + 150			°C

Notes :

- (1) Reverse Recovery Test Conditions : I_F = 0.5 A, I_R = 1.0 A, I_{rr} = 0.25 A.
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 V_{dc}

RATING AND CHARACTERISTIC CURVES (1SR124-100A ~ 1SR124-400A)

FIG.1 - REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.3 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.4 - TYPICAL FORWARD CHARACTERISTICS




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

