

[Molex.com](#)

English
日本語
한국어
简体中文

[Register | Login](#)
[My Parts \(0 items \)](#)

Search site:Search: [Go](#)

- Product Name
- Cross-Ref
- Catalog
- Literature
- Industries
- Standards
- Contact Us
- About Us
- Investors
- Careers

- Connectors
- Sockets
- I/O Connectors
- Cable Assemblies
- Fiber Optics
- Printed Circuit Products
- Industrial Products
- Lighting Products

Switch Language

- [Home](#)
- [Quick Disconnects](#)
- [Datasheet](#)

Need Assistance?

- Contact Us
- Find a Distributor
- Order Samples
- Tech Library
- Ecocare
- Electrical Models

[Printer-friendly page](#)

[Email this page](#)

Part Number:

0197054003

Status:

Active


Description:

PCB Tab Quick Disconnect, Male, for Wire, Metal Strip, Tab 6.35mm (.250") x 0.81mm (.032")

Documents: [Note - Please disable browser pop-up blockers for documents on www.molex.com](#)

[Drawing \(PDF\)](#)

[Product Specification PS-19902-010 \(PDF\)](#)



Series image - Reference only

EU RoHS
ELV and RoHS
Compliant

REACH SVHC
Contains SVHC: No

Halogen-Free
Status
Halogen-Free

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

19705Series

[Datasheet \(PDF\)](#)

[RoHS](#)

Order Products:

Part Detail: ([show all](#))

[General](#)[Physical](#)[Electrical](#)[Agency Certification](#)[Material Info](#)[Reference - Drawing Numbers](#)

General

Product Family	Quick Disconnects
Series	<u>19705</u>
Comments	Tab Support
Product Name	PCB Tab
Type	Quick Disconnect

Physical

Barrel Type	Closed
Gender	Male
Glow-Wire Compliant	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Orientation	PCB Straight Tab
Packaging Type	Reel
Plating min: Mating (μin)	150
Plating min: Mating (μm)	3.81
Plating min: Termination (μin)	150
Plating min: Termination (μm)	3.81
Polarized to Mating Part	No
Tab Thickness	0.81mm (.032")
Tab Width	6.35mm (.250")
Termination Interface: Style	Through Hole
Wire Insulation Diameter	N/A
Wire Size AWG	N/A

Electrical(Please review the Product Specification for specific details.)

Voltage - Maximum	N/A
-------------------	-----

Agency Certification

UL	E79133
----	--------

Material Info**Reference - Drawing Numbers**

Product Specification	PS-19902-010
Sales Drawing	SD-19705-400

[Help](#)