

Engineering Development Model


Voltage Controlled Oscillator

ROS-ED11929A/3

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability.

At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : CK605

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	1839		2389	MHz
Tuning Voltage	0.5		24	V
Power Output		+5		dBm
Phase Noise				
at 1 kHz offset		-78		dBc/Hz
at 10 KHz offset		-103		dBc/Hz
at 100 KHz offset		-123		dBc/Hz
at 1000 kHz offset		-143		dBc/Hz
Pulling at 12 dB _r PK-PK all phases		5		MHz
Pushing at V _{cc} =5V±0.25V		1		MHz/V
Tuning Sensitivity		12 - 30		MHz/V
Harmonic Suppression		-20		dBc
3 dB Modulation Bandwidth		125000		kHz
Supply Voltage		10.5		V
Supply Current			40	mA

MAXIMUM RATINGS	
Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Supply Voltage (V _{cc})	+12.5V
Absolute Tuning Voltage (V _{tune})	+26V

PIN CONNECTIONS	
RF OUT	10
VCC	14
V-TUNE	2
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16