

RF AMPLIFIER

MODEL *TM6667*

Available as: TM6667, 4 Pin TO-8 (T4)
 TN6667, 4 Pin Surface Mount (SM3)
 FP6667, 4 Pin Flatpack (FP4)
 BX6667, Connectorized Housing (H1)

Features

- Low Noise Figure: < 4.0 dB Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point +51 dBm (Typ.)
 Second Order Two Tone Intercept Point +45 dBm (Typ.)
 Third Order Two Tone Intercept Point +30 dBm (Typ.)

Specifications


CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency (MHz)	5 - 700	5 - 600
Gain (dB)	14	12.5 Min
Power @ 1 dB Comp. (dBm)	>15	+14.0 Min.
Reverse Isolation (dB)	-17	-16 Max.
VSWR In	<1.5:1	2.0:1 Max.
Out	<1.75:1	2.0:1 Max.
Noise figure (dB)	<4.2	5.5 Max.
Power Vdc	+15	+15
mA	<33	35 Max.

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Note: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.23	-163	5.16	-175	.09	6	.25	179
50	.22	173	5.19	168	.09	- 1	.24	176
100	.21	165	5.16	155	.09	- 4	.24	173
200	.16	149	5.09	129	.10	- 9	.25	166
300	.10	130	5.04	104	.11	-15	.25	155
400	.02	50	5.06	77	.11	-22	.25	139
500	.11	- 53	5.05	49	.12	-33	.25	120
600	.21	- 75	5.01	19	.13	-44	.27	92
700	.28	- 94	4.86	- 16	.14	-58	.34	53



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 2/5/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001