





Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	1 / 29

LIQUID CRYSTAL DISPLAY MODULE
MODEL: MTF-T057AMSLN-V1
Customer's No.:

Acceptance

Microtips Technology Inc.
 12F. No.31 Lane 169, Kang Ning St.,
 His-Chih, Taipei Hsien, Taiwan
 FAX: 886-2-26958625

Approved and Checked by

Approved by	Checked by		Made by
			



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	2 / 29

Revise Records

Rev.	Date	Contents	Written	Approved
A	11/10/2006	Initial Release	Heinz Wu	Garry Chen
B	12/15/2006	View Angle, Color Scale Modified	Heinz Wu	Garry Chen

Special Notes

Note1.	
Note2.	
Note3.	
Note4.	
Note5.	



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	3 / 29

Contents

1.	GENERAL DESCRIPTION AND FEATURES	4
1.1	Features	4
1.2	LCD Module	4
2.	MECHANICAL INFORMATION	4
3.	ELECTRICAL SPECIFICATIONS	5
3.1	Absolute Max. Ratings	5
3.2	Electrical Characteristics	7
3.3	AC Timing Characteristic of The LCD	8
3.4	Back-Light Unit.....	10
4.	OPTICAL CHARACTERISTICS	11
4.1	Optical characteristic of the LCD.....	11
4.2	Optical characteristic of the Back-Light	15
5.	I/O TERMINAL	16
5.1	Pin Assignment.....	16
5.2	Block Diagram	18
5.3	Back-light Unit (BLU).....	18
6.	DISPLAYED COLOR AND INPUT DATA	19
7.	TEST	20
8.	APPEARANCE	21
8.1	Inspection	21
8.2	Standards	22
8.3	Visual inspection	24
9.	PRECAUTIONS	25
9.1	Operation	25
9.2	Safety	25
9.3	Handling.....	25
9.4	Static electricity	27
9.5	Storage	27
9.6	Cleaning	27
9.7	Waste.....	27
10.	WARRANTY	28
11.	DIMENSIONAL OUTLINES	29



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	4 / 29

1. GENERAL DESCRIPTION AND FEATURES

MTF-T057AMSLN-V1 is a transmissive type color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching devices. This model is composed of a TFT-LCD module, a driver circuit and a back-light unit. Graphics and texts can be displayed on a QVGA 320 (W) x 3 x 240 (H) dots with 262,144 colors by supplying 18 bits data signal (6bits/each color). The following table described the features of MTF-T057AMSLN-V1.

1.1 Features

- Transmissive and back-light with nine LEDs are available.
- TN (Twisted Nematic) mode.
- Digital RGB (6bits/color) data transfer.
- Backlight-driving DC/AC inverter is not built in this module.

1.2 LCD Module

Item	Specification	Unit
Screen Size	5.7 inches	Diagonal
Display Resolution	320 (H) x 240 (V)	Dots
Active Area	115.20 (H) x 86.40 (V)	mm
Outline Dimension	144.00 (H) x 104.60 (V) x 11.00 (T)	mm
Display Mode	Normally white mode/ Transmissive/ Wide view	-
Pixel Arrangement	R,G,B Vertical Tripe	-
Surface Treatment	Hard-coating (3H)	-
Display Color	Full Colors	-
Viewing Direction	6 o'clock	-
Input Interface	Digital RGB (6bits/color) Data Transfer	-
TFT Driver	Source: HX8218A, Gate: HX8615A	-

2. MECHANICAL INFORMATION

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	--	144.00	--	mm	(1,2,3)
	Vertical (V)	--	104.60	--	mm	(2)
	Thickness (T)	--	11.00	--	mm	(1,3)
Weight		--	N/A	--	g	--

Note (1) Not include FPC. Refer to the Outline Dimension Drawing as attached.

(2) Back-light unit is included.

(3) Excluding backlight cables.



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	5 / 29

3. ELECTRICAL SPECIFICATIONS

3.1 Absolute Max. Ratings


3.1.1 Absolute Ratings of Environment

If the operating condition exceeds the following absolute maximum ratings, the TFT LCD module may be damaged permanently.

($T_a=25\pm 2^\circ\text{C}$, $V_{SS}=\text{GND}=0$)

Item	Symbol	Min.	Max.	Unit	Note
Storage temperature	T_{STG}	-30	80	$^\circ\text{C}$	(1)
Operating temperature	T_{OPR}	-20	70	$^\circ\text{C}$	(1,2,3)

Note (1) 95 % RH Max. ($40^\circ\text{C} \geq T_a$). Maximum wet-bulb temperature at 39°C or less. ($T_a > 40^\circ\text{C}$)
No condensation.



Note (2) In case of below 0° , the response time of liquid crystal (LC) becomes slower and the color of panel becomes darker than normal one. Level of retardation depends on temperature, because of LC's character

Note (3) Only operation is guaranteed at operating temperature. Contrast, response time, another display quality are evaluated at $+25^\circ\text{C}$.



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	6 / 29

3.1.2 Electrical Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark	
+3.3V	Current dissipation	V_{CC}	+3.0	+3.3	+3.6	V	Note 1
	Supply voltage	I_{CC}	--	(55)	(60)	mA	--
Permissible input ripple voltage	V_{RF}	--	--	100	mVp-p	$V_{CC} = +3.3V$	
Input voltage (Low)	V_{IL}	0	--	$0.3V_{CC}$	V	Note 2	
Input voltage (High)	V_{IH}	$0.7V_{CC}$	--	+5.5	V		
Input current (Low)	I_{OL1}	--	--	10	μA	$V_I = 0V$, Note 2	
Input current (High)	I_{OH1}	--	--	10	μA	$V_I = 3.3 \sim 5.0V$, Note 3	
	I_{OH2}	--	--	100	μA	$V_I = 3.3 \sim 5.0V$, Note 4	


Note1:

V_{CC} -turn-on conditions

$$0 < t1 \leq 20ms$$

$$0 < t2 \leq 50ms$$


$$0 < t3 \leq 1s$$



V_{CC} -dip conditions

V_{CC} -dip conditions should also follow the V_{CC} -turn-on conditions

$$T_d \leq 20ms$$



Note2: CLK, R0~R5, G0~G5, B0~B5, Hsync, Vsync, DE, R/L, U/D

Note3: CLK, R0~R5, G0~G5, B0~B5, Hsync, Vsync, R/L, U/D

Note4: DE



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	7 / 29

3.2 Electrical Characteristics

3.2.1 DC Electrical Characteristics of the TFT LCD

(Ta=25±2°C, V_{SS}=GND=0)

Item	Symbol	Min.	Typ.	Max.	Unit	Remark	
Power supply	VDD	3.0	3.3	3.6	V		
Input Voltage for logic	L Level	V _{IH}	0.7VDD	-	VDD	V	Note 1
	H Level	V _{IL}	0	-	0.3VDD	V	
Power Supply current	I _{DD}		T.B.D			Note 2	

Note1: Hsync, Vsync, DEN, DCLK, R0~R5, G0~G5, B0~B5

Note2: fV =60Hz , Ta=25°C , Display pattern : All Black



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	8 / 29

3.3 AC Timing Characteristic of The LCD

3.3.1 Timing Condition

Signal	Parameter	Symbol	Min.	Typ.	Max.	Unit.	Remark	
DCLK	DCLK period	TOSC	-	156	-	ns		
	Frequency	FOSC	-	6.4	-	MHz		
	DCLK High plus width	TCH	-	78	-	ns		
	DCLK Low plus width	TCL	-	78	-	ns		
RGB DATA	Data setup time	TSU	12	-	-	ns		
	Data hold time	THD	12	-	-	ns		
Hsync	Hsync period	TH	-	408	-	TOSC		
	Hsync pulse width	THS	5	30	-	TOSC		
	Back-Porch	THB		38		TOSC		
	Front-Porch	THF		20		TOSC		
	Hsync rising time	TCr	-	-	700	ns		
	Hsync falling time	TCf	-	-	300	ns		
Vsync	Vsync period	NTSC	-	262.5	-	TH		
		PAL	-	312.5	-	TH		
	Vsync pulse width	TVS	1	3	5	TH		
	Back-Porch	NTSC	TVB		15		TH	
		PAL			23		TH	
	Display Period	TVD		240		TH		
	Front Porch	NTSC	TVF		4.5		TH	
		PAL			46.5		TH	
	Vsync rising time	TVr	-	-	700	ns		
	Vsync falling time	TVf	-	-	1.5	μs		
	Vsync falling to Hsync rising time for odd field	THVO	1	-	-	TOSC		
Vsync falling to Hsync falling time for even field	THVE	1	-	-	TOSC			
DEN	Vsync-DEN time	NTS C	TVSE	-	18	-	TH	
		PAL	TVSE	-	26	-	TH	
	Hsync-DEN time	THE	36	68	88	TOSC		
	DEN plus width	TEP	-	320	-	TOSC		


Note : If DEN is fixed to low, the SYNC mode is used. Otherwise DE mode is used. When SYNC mode is used, 1st data start from 68th CLK after Hsync falling




Messrs.

Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	9 / 29

3.3.2 Horizontal Display Timing




3.3.3 Vertical Display Timing



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	10 / 29

3.3.4 Hsync and Vsync Timing



3.4 Back-Light Unit

The Back-light system is an edge-lighting type with 9 white LED(Light Emitting Diode)s. The characteristics of 9 white LEDs are shown in the following tables.

(Ta= Room Temp)

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Current	I_B	-	270	300	mA	(1)
Power Consumption	P_{BL}	-	-	1890	mW	(2)

Note (1) 9 white LEDs parallel type.

(2) Where $I_B = 270\text{mA}$, $V_F = 7$, $P_{BL} = V_F \times I_B$



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	11 / 29

4. OPTICAL CHARACTERISTICS

4.1 Optical characteristic of the LCD

The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state with the methods shown in Note (1).

Measuring equipment: LCD-5000, BM-5A, BM-7, PR-650, EZ-Contrast

Item		Symbol	Condition	Min	Type	Max	Unit	Note	
Threshold voltages		V _{sat}	--	--	(2.58)	--	V		
		V _{th}	--	--	(1.57)	--	V		
Transmittance		T (%)	--	--	8.1	--		Note.	
Brightness				--	(550)	--	cd/m ²		
Response time		T _R	θ=0°	-	15	30	ms	Note.	
		T _F		--	35	50	ms		
Contrast ratio		CR	At optimized viewing angle	(150)	(250)	--	--	Note.	
Color Gamut		S (%)	--	--	(42%)	--	--	(C-light)	
Color Chromaticity (CIE 1931)		Red	R _x	θ=0° Normal Viewing Angle	0.610	0.640	0.670	-	Note.
			R _y		0.314	0.344	0.374		
		Green	G _x		0.268	0.298	0.328	-	
			G _y		0.553	0.583	0.613		
		Blue	B _x		0.107	0.137	0.167	-	
			B _y		0.139	0.159	0.179		
		White	W _x		0.282	0.312	0.342	-	
			W _y		0.319	0.349	0.379		
Viewing Angle (6H)		Hor.	θ _R	CR≥10	-	(65)	-	Degree	Note.
			θ _L		-	(65)	-		
		Ver.	φ _H		--	(50)	--		
			φ _L		--	(65)	--		

Note : Definition of Transmittance (T%)
 $T = \text{Aperture Ratio (TFT)} \times W_y \text{ (CF)}$



Microtips Technology Inc.


Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	12 / 29

a. Test equipment setup

After stabilizing and leaving the panel alone at a given temperature for 30 minutes, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7(fast) with a viewing angle of 2° at a distance of 50cm and normal direction.

b. Definition of response time: TR and TF

The response time is defined as the following figure and shall be measured by switching the input signal for “black” and “white”.



c. Definition of contrast ratio:

$$\text{Contrast Ratio (CR)} = \frac{\text{Brightness measured when LCD is at "white state"}}{\text{Brightness measured when LCD is at "black state"}}$$

White $V_i = V_{i50\%} \pm 1.5V$

Black $V_i = V_{i50\%} \text{ m } 2.0V$

"±" means that the analog input signal swings in phase with V_{COM} signal.

"m" means that the analog input signal swings out of phase with V_{COM} signal.

$V_{i50\%}$: The analog input voltage when transmission is 50%.

The 100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened.


d. Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	13 / 29

e. View Angle



f. Definition of Luminance of White: Luminance of white at the center points


Light Source of Back-Light Unit	LED Type
---------------------------------	----------

g. Definition of White Uniformity

$$\text{White Uniformity} = \frac{\text{Min. luminance of white among 5-points}}{\text{Max. luminance of white among 5-points}} \times 100\%$$

h. The definition of Color Gamut -Color Chromaticity CIE 1931 (Graphic-7)
Color coordinate of white & red, green, blue at center point.

$$\text{Color Gamut : } S(\%) = (\text{RGB Triangle Area} / \text{NTSC Triangle Area}) \times 100$$



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	14 / 29


i. Optical Measurement and Equipment

Reflective Mode

The Measuring condition and equipments for this mode are below:

Measuring condition

- $l = 550\text{mm}$ (typical), 1000mm (max) / d & The θ : No emission of light-source with angle from Lamp or others
- Light source : Standard C light-source (Solar light)
- Dark room : Not essential (Required exclusion of direct light effecting on the sample)



Transmissive Mode

No equipment available

Brightness Measurement Point

The Measuring condition and equipments for the brightness of LED Backlight are below:

- Measuring condition

- Measuring after LED's are turned on for 5 minutes
- Spot size = 2mm
- Distance between module and equipment = 550mm



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	15 / 29

4.2 Optical characteristic of the Back-Light

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Luminance (12 points AVG.)	IV	7000	-	-	cd/m ²	-
Color	-		White		-	-
Uniformity	U	80	-	-	%	-
Lighting type	Side Lighting					

Note (1) The measurement instrument is BM-7 luminance color-meter the measuring distance is 500±20mm.

The uniformity definition (Min. brightness / Max. brightness) x 100%



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	16 / 29

5. I/O TERMINAL

5.1 Pin Assignment


Pin No.	Symbol	I/O	Function	Remark
1	DGND	-	GND	
2	DCLK	I	Clock signal for sampling each data signal	
3	Hsync	I	Horizontal synchronous signal (Negative)	
4	Vsync	I	Vertical synchronous signal (Negative)	
5	GND	I	GND	
6	R0	I	RED data signal (LSB)	
7	R1	I	RED data signal	
8	R2	I	RED data signal	
9	R3	I	RED data signal	
10	R4	I	RED data signal	
11	R5	I	RED data signal (MSB)	
12	GND	-	GND	
13	G0	I	GREEN data signal (LSB)	
14	G1	I	GREEN data signal	
15	G2	I	GREEN data signal	
16	G3	I	GREEN data signal	
17	G4	I	GREEN data signal	
18	G5	I	GREEN data signal (MSB)	
19	GND	-	GND	
20	B0	I	BLUE data signal(LSB)	
21	B1	I	BLUE data signal	
22	B2	I	BLUE data signal	
23	B3	I	BLUE data signal	
24	B4	I	BLUE data signal	
25	B5	I	BLUE data signal(MSB)	
26	GND	-	GND	
27	DEN	I	Signal to settle the horizontal display position (Positive)	Note5-1
28	VDD	-	+ 3.3V power supply	
29	VDD	-	+ 3.3V power supply	
30	LRC	I	Horizontal display mode select signal L: Normal H: Left / Right reverse mode	Note5-2
31	UDC	I	Vertical display mode select signal H: Normal L: Up / Down reverse mode	Note5-3
32	NC	-	No Connection	
33	GND	I	GND	

Note5-1 The horizontal display start timing is settled in accordance with a rising timing of ENAB signal. In case ENAB is fixed "Low", the horizontal start timing is determined. Don't keep ENAB "High" during operation.



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	17 / 29


Note5-2,3




R/L = L, U/D = H



R/L = H, U/D = H



R/L = L, U/D = L




R/L = H, U/D = L



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	18 / 29

5.2 Block Diagram



5.3 Back-light Unit (BLU)

Pin No.	Symbol	Function	Remark
1	LEDA	Power Supply for LED backlight	
2	LEDK	GND for LED backlight	



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	19 / 29

6. DISPLAYED COLOR AND INPUT DATA

	Color & Gray Scale	Data Signal																	
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0
Basic Color	Black	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red(0)	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Green(0)	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Blue(0)	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	Cyan	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Yellow	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	White	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Red	Black	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red(62)	1	1	1	1	1	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red(61)	1	1	1	1	0	1	1	1	1	1	1	1	1	1	1	1	1	1
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(31)	1	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(1)	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red(0)	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0
Green	Black	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Green(62)	1	1	1	1	1	1	1	1	1	1	1	0	1	1	1	1	1	1
	Green(61)	1	1	1	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(31)	1	1	1	1	1	1	1	0	0	0	0	1	1	1	1	1	1	1
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(1)	1	1	1	1	1	1	0	0	0	0	0	1	1	1	1	1	1	1
	Green(0)	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
Blue	Black	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Blue(62)	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
	Blue(61)	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	1
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(31)	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(1)	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	1
	Blue(0)	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0

0 : Low level voltage, 1 :High level voltage

Each basic color can be displayed in 64 gray scales from 6 bit data signals. With the combination of total 18 bit data signals, the 262,144-color display can be achieved on the screen.



Microtips Technology Inc.

Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	20 / 29

7. TEST


No change on display and in operation under the following test condition.

Condition: Unless otherwise specified, tests will be conducted under the following condition.

Temperature: $20 \pm 25^\circ\text{C}$

Humidity: $65 \pm 5\% \text{RH}$

Tests will be not conducted under functioning state.

No.	Parameter	Condition	Notes
1	High Temperature Operating	$60^\circ\text{C} \pm 2^\circ\text{C}$, 96hrs (Operation state)	
2	Low Temperature Operating	$0^\circ\text{C} \pm 2^\circ\text{C}$, 96hrs (Operation state)	1
3	High Temperature Storage	$70^\circ\text{C} \pm 2^\circ\text{C}$, 96hrs	2
4	Low Temperature Storage	$-20^\circ\text{C} \pm 2^\circ\text{C}$, 96hrs	1,2
5	Damp Proof Test	$40^\circ\text{C} \pm 2^\circ\text{C}$, 90~95%, 96hrs	1,2
6	Vibration Test	Total fixed amplitude: 1.5mm Vibration Frequency: 10~55Hz One cycle 60 seconds to 3 direction of X, Y, Z each 15 minutes.	3
7.	Shock Test	To be measured after dropping from 60cm high on the concrete surface in packing state. 	

- Notes:
1. No dew condensation to be observed.
 2. The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.
 3. Vibration test will be conducted to the product itself without putting I in a container.




Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	21 / 29


8. APPEARANCE

8.1 Inspection

The distance between the eyes and the sample shall be more than 30cm. All directions for inspecting the sample should be within 45° against perpendicular line.



Definition of Applicable Zones



A Zone : Active display area

B Zone : Area from outside of "A Zone" to validity viewing area

C Zone : Rest parts

A Zone + B Zone = Validity viewing area

(a) Operating Inspection

The function and appearance shall be inspected in the condition of

- under 750 lx or over light Reflective Type.
- Using over Backlight unit Transflective Type, Transmissive Type

Condition of judgment

In case of no gradation display it judges by applied On/Off voltage or optimal contrast.

In case of gradation display it judges by contrast that the bad point is able to confirm best.

(b) Appearance Inspection

The appearance shall be inspected in the condition of

- under 500 lx or over light Reflective Type.
- Using over Backlight unit Transflective Type, Transmissive Type

(c) Inspection Environment

Inspection environment it carried out with 250 lx or less in principles.



Microtips Technology Inc.



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	22 / 29

8.2 Standards

No.	Parameter	Criteria																																																															
1	G Line	Nothing																																																															
2	S Line	Nothing																																																															
3	Leak	Nothing																																																															
4	Bright and Dark Spot	<p>Inspection Criteria Include below with the common inspection. Luminance: under 250 [lx] Distance: 30 ~ 40 [cm] (Perpendicular from panel surface) Time: 5 [S] (After ND filter has been placed)</p> <table border="1"> <thead> <tr> <th>Zone</th> <th colspan="2">Acceptable Number</th> </tr> </thead> <tbody> <tr> <td rowspan="3">A</td> <td>Bright Spot</td> <td>2</td> </tr> <tr> <td>Adjacent Dot</td> <td>0</td> </tr> <tr> <td>Dark Dot</td> <td>3</td> </tr> <tr> <td>BM</td> <td>Bright Spot</td> <td>0</td> </tr> </tbody> </table> <p>* Adjacent Dot Horizontal and Vertical Continuous Bright Dots * Bright spot is definition as follows. * Any things that can be seen through 10% transmission ND filter when black signal is inputted.</p>	Zone	Acceptable Number		A	Bright Spot	2	Adjacent Dot	0	Dark Dot	3	BM	Bright Spot	0																																																		
Zone	Acceptable Number																																																																
A	Bright Spot	2																																																															
	Adjacent Dot	0																																																															
	Dark Dot	3																																																															
BM	Bright Spot	0																																																															
5	Contrast Variation	Not to be conspicuous defects. Limit sample shall be determined by the arising demand.																																																															
6	Black and White Spots, Foreign Material in Polarizer and LR/AR Coat Bright point	<p>(1) Round Shape</p> <table border="1"> <thead> <tr> <th rowspan="2">Dim. (mm)</th> <th>Zone</th> <th colspan="2">Acceptable Number</th> </tr> <tr> <th></th> <th>A</th> <th>BM</th> </tr> </thead> <tbody> <tr> <td>$D \leq 0.10$</td> <td></td> <td colspan="2">Disregard</td> </tr> <tr> <td>$0.10 < D \leq 0.15$</td> <td></td> <td colspan="2">4</td> </tr> <tr> <td>$0.15 < D \leq 0.20$</td> <td></td> <td colspan="2">2</td> </tr> <tr> <td>$0.20 < D$</td> <td></td> <td colspan="2">0</td> </tr> </tbody> </table> <p>(2) Line Shape</p> <table border="1"> <thead> <tr> <th rowspan="2">X(mm)</th> <th rowspan="2">Y(mm)</th> <th colspan="2">Zone</th> <th colspan="2">Acceptable Number</th> </tr> <tr> <th>A</th> <th>BM</th> <th>A</th> <th>BM</th> </tr> </thead> <tbody> <tr> <td>-</td> <td>$W \leq 0.01$</td> <td colspan="4">Disregard</td> </tr> <tr> <td>$L \leq 2.0$</td> <td>$W \leq 0.02$</td> <td colspan="4">2</td> </tr> <tr> <td>$L \leq 1.0$</td> <td>$W \leq 0.03$</td> <td colspan="4">1</td> </tr> <tr> <td>$L > 1.0$</td> <td>-</td> <td colspan="4">0</td> </tr> <tr> <td>-</td> <td>$W > 0.05$</td> <td colspan="4">4</td> </tr> </tbody> </table> <p>X: Length Y: Width</p> <p>Total number of this defect (add up round shape and line shape) shall be two or less pieces. Limit sample shall be determined by the arising demand.</p>	Dim. (mm)	Zone	Acceptable Number			A	BM	$D \leq 0.10$		Disregard		$0.10 < D \leq 0.15$		4		$0.15 < D \leq 0.20$		2		$0.20 < D$		0		X(mm)	Y(mm)	Zone		Acceptable Number		A	BM	A	BM	-	$W \leq 0.01$	Disregard				$L \leq 2.0$	$W \leq 0.02$	2				$L \leq 1.0$	$W \leq 0.03$	1				$L > 1.0$	-	0				-	$W > 0.05$	4			
Dim. (mm)	Zone	Acceptable Number																																																															
		A	BM																																																														
$D \leq 0.10$		Disregard																																																															
$0.10 < D \leq 0.15$		4																																																															
$0.15 < D \leq 0.20$		2																																																															
$0.20 < D$		0																																																															
X(mm)	Y(mm)	Zone		Acceptable Number																																																													
		A	BM	A	BM																																																												
-	$W \leq 0.01$	Disregard																																																															
$L \leq 2.0$	$W \leq 0.02$	2																																																															
$L \leq 1.0$	$W \leq 0.03$	1																																																															
$L > 1.0$	-	0																																																															
-	$W > 0.05$	4																																																															
7	Color	Not to be conspicuous defects.																																																															



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	23 / 29

	Variation	Limit sample shall be determined by the arising demand. However, about the color patches shall be two pieces or less which are same level as the limit sample.																	
8	Air Bubbles (between glass and polarizer)	<table border="1"> <thead> <tr> <th rowspan="2">Zone Dim. (mm)</th> <th colspan="2">Acceptable Number</th> </tr> <tr> <th>A</th> <th>BM</th> </tr> </thead> <tbody> <tr> <td>$D \leq 0.10$</td> <td colspan="2">Disregard</td> </tr> <tr> <td>$0.10 < D \leq 0.15$</td> <td colspan="2">1</td> </tr> <tr> <td>$0.15 < D \leq 0.20$</td> <td colspan="2">1</td> </tr> <tr> <td>$0.20 < D$</td> <td colspan="2">0</td> </tr> </tbody> </table> <p>The polarizer edge has not floated. Limit sample shall be determined by the arising demand.</p>	Zone Dim. (mm)	Acceptable Number		A	BM	$D \leq 0.10$	Disregard		$0.10 < D \leq 0.15$	1		$0.15 < D \leq 0.20$	1		$0.20 < D$	0	
Zone Dim. (mm)	Acceptable Number																		
	A	BM																	
$D \leq 0.10$	Disregard																		
$0.10 < D \leq 0.15$	1																		
$0.15 < D \leq 0.20$	1																		
$0.20 < D$	0																		
9	Polarizer Scratches, Stroke Marks	Not to be conspicuous defects. Limit sample shall be determined by the arising demand.																	
10	Polarizer Dirts	If the stains are removed easily from LCDP surface, the module is not defective.																	
11	Chipped glass	<p>(1) Other than electrode pad areas and corner areas</p>  <table border="1"> <thead> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>≤ 5.0</td> <td></td> <td>$\leq 1/2t$</td> </tr> </tbody> </table> <p>(2) Other than electrode pad areas</p>  <table border="1"> <tbody> <tr> <td>$X \leq 1.5 \text{ \& } Y \leq 0.5$</td> </tr> <tr> <td>or</td> </tr> <tr> <td>$X \leq 0.5 \text{ \& } Y \leq 1.5$</td> </tr> <tr> <td>* The direction of board thickness is disregard</td> </tr> </tbody> </table> <p>* For LCD module holder It is disregard. When it has no problem for appearance, reliability and progressiveness. * For LCD module without holder. The back side is disregard. When it has no problem for reliability and progressiveness. * It is not approved when a glass chip occurs with the part of the seal, wiring and terminal.</p>	X	Y	Z	≤ 5.0		$\leq 1/2t$	$X \leq 1.5 \text{ \& } Y \leq 0.5$	or	$X \leq 0.5 \text{ \& } Y \leq 1.5$	* The direction of board thickness is disregard							
X	Y	Z																	
≤ 5.0		$\leq 1/2t$																	
$X \leq 1.5 \text{ \& } Y \leq 0.5$																			
or																			
$X \leq 0.5 \text{ \& } Y \leq 1.5$																			
* The direction of board thickness is disregard																			



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	24 / 29

8.3 Visual inspection


Should be checked at $22\pm 2^{\circ}\text{C}$, $50\pm 5\%\text{RH}$, 300-500 lux, 300mm distance, within 80 degree viewing angle in 4 directions, at typical LED current.

8.3.1 Outside of effective lighting area

Item	Condition	Specification
Particle	Non-Operation	Cannot be shown easily.
Non-lighting, Unstable lighting	Operation	None
Contamination and defects of mold frame	Non-Operation	None

8.3.2 Inside of effective lighting area

Item	Condition	Specification
Black spot, Particle	Operation	$D < 0.10$: OK (not within 15mm) $0.10 \leq D < 0.20$: 2EA OK (not within 15mm) $D \geq 0.20$: NG $D = (a+b)/2$
Bright spot, Bright Line, Dim spot Scratch, Newton Ring	Operation	Should not be shown on the glass panel after panel ass'y
Stain	Operation	Should not be shown on the glass panel after panel ass'y



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	25 / 29

9. PRECAUTIONS





9.1 Operation

Burn-in sometimes happens when the same character was displayed at along time. Therefore, to prevent Burn-in, it is recommended to set up a Screen-saver function.

9.2 Safety

The liquid crystal in the LCD is poisonous, DO NOT put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

9.3 Handling

	<p>a. The LCD module shall be installed flat, without twisting or bending.</p> <p>b. COF or FPC has narrow pattern width, so easily become open circuit by external force. DO NOT apply pressure to COF or FPC especially in bending area.</p>
	<p>c. To avoid damage in appearance or malfunction, DO NOT subject the module to mechanical shock or to excessive force on its surface.</p>
	<p>d. The polarizer attached to the display is very easy to damage, handle it with care to avoid scratching.</p>
	<p>e. To avoid contamination on the display surface, DO NOT touch the display surface with bare hands.</p> <p>f. Provide a space so that the LCD module does not come into contact with other components.</p>



Messrs.

Product Specification
For Only

Model:

MTF-T057AMSLN-V1

Rev. No.







B

Issued Date.

NOV 10, 06

Page.

26 / 29

	<p>g. To protect the LCD panel from external pressure, put covering glass (acrylic board or similar board) to keep appropriate space between them.</p>
	<p>h. Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.</p>
	<p>i. Property of semiconductor devices may be affected when they are exposed to light possibly resulting in malfunctioning of the ICs. To prevent such malfunctioning of the ICs, your design and mounting layout done are so that the IC is not exposed to light in actual use.</p>
	<p>j. Strong light exposure causes degradation of color filter. It may not recover</p>
	<p>k. DO NOT contact with water to avoid Metal corrosion.</p> <p>l. When it is not in use, the screen must be turned off or the pattern must be frequently changed by a screen saver. If it displays the same pattern for a long period of time, brightness down/image sticking may develop due to the LCD structure.</p>
	<p>m. Never disassemble LCD product under any circumstances. If unqualified operators or users assemble the product after disassembling it, it may not function or its operation may be seriously affected.</p>




Microtips Technology Inc.


Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	27 / 29

9.4 Static electricity


Since a module is composed of electronic circuits, it is not strong to electrostatic discharge.

	<ol style="list-style-type: none"> The LCD module shall be installed flat, without twisting or bending. Ground soldering iron tips, tools and testers when they operate. Ground your body when handling the products. DO NOT apply voltage to the input terminal without applying power supply. DO NOT apply voltage that exceeds the absolute maximum rating. Store the products in an anti-electrostatic container. Peel off protect tape, attached to polarizer, slowly to minimize ESD damage.
---	--


9.5 Storage

	<p>Store the products in a dark place at +5 ~ +25 degree C, low humidity (50%RH or less). DO NOT store the products in an atmosphere containing organic solvents or corrosive gases.</p>
---	--

9.6 Cleaning

	<ol style="list-style-type: none"> DO NOT wipe the polarizer with dry cloth, as it might cause scratch. Wipe the polarizer with a soft cloth soaked with petroleum IPA, other chemical might damage.
---	--

9.7 Waste

	<p>When dispose of LCD module, manage it at the production waste according to the relevant laws and regulations.</p>
---	--



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			<i>B</i>	<i>NOV 10, 06</i>	<i>28 / 29</i>

10. WARRANTY


This product has been manufactured to your company's specifications as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment, we cannot take responsibility if the product is used in medical devices, nuclear power control equipment, aerospace equipment, fire and security systems, or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required. If the product is to be used in any of the above applications, we will need to enter into a separate product liability agreement.

- 1 We cannot accept responsibility for any defect, which may arise from additional manufacturing of the product (including disassembly and reassembly), after product delivery.
- 2 We cannot accept responsibility for any defect, which may arise after the application of strong external force to the product.
- 3 We cannot accept responsibility for any defect, which may arise due to the application of static electricity after the product has passed your company's acceptance inspection procedures.
- 4 We cannot accept responsibility for industrial property, which may arise through the use of your product, with exception to those issues relating directly to the structure or method of manufacturing of our product. Microtips-origin longer than one year from Microtips production.



Messrs.					
Product Specification For Only	Model:	MTF-T057AMSLN-V1	Rev. No.	Issued Date.	Page.
			B	NOV 10, 06	29 / 29

11. DIMENSIONAL OUTLINES



Microtips Technology Inc.