


## **HRW0502A**

### ■ Features

- Low forward voltage drop and suitable for high efficiency rectifying.
- MPAK package is suitable for high density surface mounting and high speed assembly.



### ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V <sub>RRM</sub>	20	V
Average rectified current	I <sub>o</sub>	500	mA
Non-repetitive peak forward surge current	I <sub>FSM</sub> (Note 1)	5	A
Junction temperature	T <sub>j</sub>	125	°C
Storage temperature	T <sub>stg</sub>	-55 to + 125	°C

Note

1. 10msec sine wave 1 pulse

### ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V <sub>F</sub>	I <sub>F</sub> = 500 mA			0.40	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> = 20 V			200	µ A
Capacitance	C	V <sub>R</sub> = 0 V, f = 1MHz		120		pF
Thermal resistance	R <sub>th(j-a)</sub>	Polyimide board		340		°C/W

### ■ Marking

Marking	S10
---------	-----