

**CABLE-50/4FLK14/ 3,0M/YUC**

Order No.: 2314668

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2314668>

Assembled round cable with a 50-pos. molded socket strip and four 14-pos. socket strips, for splitting 32 channels into 4 x 8 channels, number of positions: 50/ 4 x 14, the cable is suitable for the ADV551 and ADV151 boards. Length of cable: 3.0 m

**Commercial data**

EAN	4046356147309
Pack	1 pcs.
Customs tariff	85444290
Weight/Piece	0.616 KG
Catalog page information	Page 223 (IF-2009)

**Product notes**

WEEE/RoHS-compliant since:  
07/19/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General**

Nominal voltage $U_N$	30 V DC
Max. current carrying capacity per path	500 mA (Up to 55°C ambient temperature)
Max. conductor resistance	0.16 $\Omega$ /m

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	50
Number of positions, control side	50
Number of connectors, control side	1
Number of positions, module side	14
Number of connectors, modul side	4
Fixed cable length	3 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	11 mm

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact  
Technical modifications reserved;