



- NOTES:
1. ALL DIMENSION IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC  
350mA, 110V AC/DC
  5. CONTACT RATING (NON-SWITCHING) 5A
  6. OPERATING FORCE: 425±100 CM/STANDARD
  7. OPERATING TEMP: -30° to 85°C
  8. CIRCUIT SP: 5 POSITIONS, 30° INDEX.
  9. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
  10. DESIGNATE MAJOR DIMENSIONS
  11. LOCK NUT AND WASHER NOT SHOWN.

**E-SWITCH**

REV. A		11E52		RELEASED FOR PRODUCTION		05/09/01		RJC	
REV. ECN No.		DESCRIPTION		DATE		CHK'D		SCALE	
1.5:1		KC-15-B-02-N-P-F (B=31.5mm W/Slot)		DATE		DR		DWG	
05/08/01		PML		G510252		REV		A	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED