


## 4-bit dual supply level translator without direction control pin

Datasheet — production data

### Features

- 42 MHz: 84 Mbps (max.) data rate at  $V_L = 1.8 \text{ V}$ ,  $V_{CC} = 3.3 \text{ V}$
- Bi-directional level translation without direction control pin
- Wide voltage range ( $V_{CC} \geq V_L$ ):
  - $V_L$  ranges from 1.65 to 3.6 V
  - $V_{CC}$  ranges from  $V_L$  to 5.5 V
- Power-down mode feature - when  $V_{CC}$  supply is off, all I/Os are in high impedance
- Totem pole driving
- 5.5 V tolerant enable pin
- ESD performance on all pins:  $\pm 2 \text{ kV}$  HBM
- Small package and footprint QFN16 (2.6 x 1.8 mm) package



### Applications

- Low-voltage system level translation
- Mobile phones and other mobile devices

### Description

The ST2149 is a 4-bit dual supply level translator which provides the level shifting capability to allow data transfer in a multi-voltage system. Externally applied voltages,  $V_{CC}$  and  $V_L$ , set the logic levels on either side of the device. Its architecture allows bi-directional level translation without a control pin.

The ST2149 accepts  $V_L$  from 1.65 to 3.6 V and  $V_{CC}$  from 1.65 to 5.5 V, making it ideal for data transfer between low-voltage ASICs/PLD and higher voltage systems. This device has a tri-state output mode which can be used to disable all I/Os.

The ST2149 supports power-down mode when  $V_{CC}$  is grounded/floating or when the device is disabled via the OE pin.

**Table 1. Device summary**

Order code	Package	Packaging
Root part number 1QTR	QFN16 (2.6 x 1.8 mm)	Tape and reel (3000 parts per reel)

## Contents

<b>1</b>	<b>Pin settings</b>	<b>5</b>
1.1	Pin connection	5
1.2	Pin description	6
<b>2</b>	<b>Logic diagram</b>	<b>7</b>
	Device block diagrams	8
<b>3</b>	<b>Supplementary notes</b>	<b>9</b>
3.1	Driver requirements	9
3.2	Load driving capability	9
3.3	Power-off feature	9
3.4	Truth table	9
<b>4</b>	<b>Maximum ratings</b>	<b>10</b>
	Recommended operating conditions	10
<b>5</b>	<b>Electrical characteristics</b>	<b>11</b>
	AC characteristics	13
<b>6</b>	<b>Test circuit</b>	<b>16</b>
<b>7</b>	<b>Package mechanical data</b>	<b>18</b>
<b>8</b>	<b>Revision history</b>	<b>22</b>

## List of tables

Table 1.	Device summary . . . . .	1
Table 2.	Pin description . . . . .	6
Table 3.	Truth table . . . . .	9
Table 4.	Absolute maximum ratings . . . . .	10
Table 5.	Recommended operating conditions . . . . .	10
Table 6.	DC characteristics . . . . .	11
Table 7.	AC characteristics - test conditions: $V_L = 1.65 - 1.95$ V . . . . .	13
Table 8.	AC characteristics - test conditions: $V_L = 2.3 - 2.7$ V . . . . .	14
Table 9.	AC characteristics - test conditions: $V_L = 3.0 - 3.6$ V . . . . .	14
Table 10.	Test circuit switches . . . . .	16
Table 11.	Waveform symbol value . . . . .	16
Table 12.	Mechanical data for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch . . . . .	19
Table 13.	Document revision history . . . . .	22


## List of figures

Figure 1.	Pin connection (top through view) .....	5
Figure 2.	Logic block diagram .....	7
Figure 3.	ST2149 block diagram .....	8
Figure 4.	Application block diagram.....	8
Figure 5.	Test circuit .....	16
Figure 6.	Waveform - propagation delay ( $f = 1$ MHz, 50% duty cycle). ....	17
Figure 7.	Waveform - output enable and disable time ( $f = 1$ MHz, 50% duty cycle) .....	17
Figure 8.	Package outline for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch .....	18
Figure 9.	Footprint recommendation for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch .....	19
Figure 10.	Carrier tape for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch .....	20
Figure 11.	Reel information for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch .....	21

# 1 Pin settings

## 1.1 Pin connection

Figure 1. Pin connection (top through view)




## 1.2 Pin description

Table 2. Pin description

Pin number	Symbol	Name and function
1	I/O <sub>VL2</sub>	Data input/output
2	OE	Output enable
3	I/O <sub>VL3</sub>	Data input/output
4	I/O <sub>VL4</sub>	Data input/output
5	NC	No connection
6	V <sub>L</sub>	Supply voltage
7	V <sub>CC</sub>	Supply voltage
8	NC	No connection
9	I/O <sub>VCC4</sub>	Data input/output
10	I/O <sub>VCC3</sub>	Data input/output
11	GND	Ground
12	I/O <sub>VCC2</sub>	Data input/output
13	I/O <sub>VCC1</sub>	Data input/output
14	V <sub>CC</sub>	Supply voltage
15	V <sub>L</sub>	Supply voltage
16	I/O <sub>VL1</sub>	Data input/output

## 2 Logic diagram


Figure 2. Logic block diagram



AM04077V2


## Device block diagrams

**Figure 3.** ST2149 block diagram



AM04078V2

**Figure 4.** Application block diagram



AM04079V2

### 3 Supplementary notes

#### 3.1 Driver requirements

For proper operation, the driver from each side of the device must be able to source and sink a minimum of 1 mA current. The device architecture requires the driver to source/sink maximum current of ( $V_{CC}/4$ ) mA to/from the weak 4 k $\Omega$  output buffer.

#### 3.2 Load driving capability

To support the architecture that allows level translation without the direction pin, the one-shot transistor is turned ON only during state transition at the output side. After the one-shot transistor is turned OFF, only the 4 k $\Omega$  resistor maintains the state. So, a resistive load or pull-up resistor less than 50 k $\Omega$  is not recommended for proper operation.

#### 3.3 Power-off feature

In some applications it may be required to turn off one of the power supplies powering up the level translator. The device is automatically disabled when  $V_{CC}$  supply is turned OFF, even if the OE pin is set to HIGH (enabled). In this mode, all I/Os are in high impedance state.

#### 3.4 Truth table

**Table 3. Truth table**

		Bi-directional Input/output	
Enable			
OE		I/O <sub>VCC</sub>	I/O <sub>VL</sub>
H <sup>(1)</sup>		H <sup>(2)</sup>	H <sup>(1)</sup>
H <sup>(1)</sup>		L	L
L		Z <sup>(3)</sup>	Z <sup>(3)</sup>

1. High-level  $V_L$  power supply referred.
2. High-level  $V_{CC}$  power supply referred.
3. Z = high impedance.

## 4 Maximum ratings

Stressing the device above the ratings listed in [Table 4](#) may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those indicated in [Recommended operating conditions](#) of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

**Table 4. Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$V_L$	Supply voltage	-0.3 to 4.6	V
$V_{CC}$	Supply voltage	-0.3 to 6.5	V
$V_{OE}$	DC control input voltage	-0.3 to 6.5	V
$V_{I/OVL}$	DC I/O <sub>VL</sub> input voltage ( $OE = GND$ or $V_L$ )	-0.3 to $V_L + 0.3$	V
$V_{I/OVCC}$	DC I/O <sub>VCC</sub> input voltage ( $OE = GND$ or $V_L$ )	-0.3 to $V_{CC} + 0.3$	V
$I_{IK}$	DC input diode current	-20	mA
$I_{I/OVL}$	DC output current	$\pm 25$	mA
$I_{I/OVCC}$	DC output current	$\pm 25$	mA
$I_{SCTOUT}$	Short-circuit duration, continuous	40	mA
$P_D$	Power dissipation	500	mW
$T_{STG}$	Storage temperature	-65 to 150	°C
$T_L$	Lead temperature (10 seconds)	300	°C
ESD	Electrostatic discharge protection (HBM)	$\pm 2$	kV

## Recommended operating conditions

**Table 5. Recommended operating conditions**

Symbol	Parameter	Min.	Typ.	Max.	Unit
$V_L$	Supply voltage	1.65	–	3.6	V
$V_{CC}$	Supply voltage	$V_L$	–	5.5	V
$V_{OE}$	Input voltage (OE output enable pin, $V_L$ power supply referred)	0	–	3.6	V
$V_{I/OVL}$	I/O <sub>VL</sub> voltage	0	–	$V_L$	V
$V_{I/OVCC}$	I/O <sub>VCC</sub> voltage	0	–	$V_{CC}$	V
$T_{OP}$	Operating temperature	-40	–	85	°C
dt/dV	Input rise and fall time	0	–	1	ns/V

## 5 Electrical characteristics

Over recommended operating conditions unless otherwise noted. All typical values are at  $T_A = 25^\circ\text{C}$ .

**Table 6. DC characteristics**

Symbol	Parameter	$V_L$	$V_{CC}$	Test conditions	Value					Unit	
					$T_A = 25^\circ\text{C}$			$-40 \text{ to } 85^\circ\text{C}$			
					Min.	Typ.	Max.	Min.	Max.		
$V_{IHL}$	High-level input voltage ( $I/O_{VL}$ )	1.65	1.65 to 5.5		1.16	—	—	1.16	—	V	
		1.8			1.26	—	—	1.26	—		
		2.5			1.75	—	—	1.75	—		
		3.0			2.10	—	—	2.10	—		
		3.6			2.52	—	—	2.52	—		
		1.65			—	—	0.50	—	0.50		
$V_{ILL}$	Low-level input voltage ( $I/O_{VL}$ )	1.8	1.65 to 5.5		—	—	0.54	—	0.54	V	
		2.5			—	—	0.75	—	0.75		
		3.0			—	—	0.90	—	0.90		
		3.6			—	—	1.08	—	1.08		
		1.65			1.16	—	—	1.16	—		
$V_{IHC}$	High-level input voltage ( $I/O_{VCC}$ )	1.8	1.65 to 3.6		1.26	—	—	1.26	—	V	
		2.5			1.75	—	—	1.75	—		
		3.0			2.10	—	—	2.10	—		
		3.6			2.52	—	—	2.52	—		
		4.3			3.01	—	—	3.01	—		
		5.5			3.85	—	—	3.85	—		
		1.65			—	—	0.50	—	0.50		
$V_{ILC}$	Low-level input voltage ( $I/O_{VCC}$ )	1.8	1.65 to 3.6		—	—	0.54	—	0.54	V	
		2.5			—	—	0.75	—	0.75		
		3.0			—	—	0.90	—	0.90		
		3.6			—	—	1.08	—	1.08		
		4.3			—	—	1.29	—	1.29		
		5.5			—	—	1.65	—	1.65		

**Table 6. DC characteristics (continued)**

Symbol	Parameter	V <sub>L</sub>	V <sub>CC</sub>	Test conditions	Value					Unit	
					T <sub>A</sub> = 25 °C			-40 to 85 °C			
					Min.	Typ.	Max.	Min.	Max.		
V <sub>IH_OE</sub>	High-level input voltage (OE)	1.65	1.65 to 5.5		1.16	—	—	1.16	—	V	
		1.8			1.26	—	—	1.26	—		
		2.5			1.75	—	—	1.75	—		
		3.0			2.10	—	—	2.10	—		
		3.6			2.52	—	—	2.52	—		
		1.65			—	—	0.50	—	0.50		
V <sub>IL_OE</sub>	Low-level input voltage (OE)	1.8	1.65 to 5.5		—	—	0.54	—	0.54	V	
		2.5			—	—	0.75	—	0.75		
		3.0			—	—	0.90	—	0.90		
		3.6			—	—	1.08	—	1.08		
V <sub>OHL</sub>	High-level output voltage (I/O <sub>VL</sub> )	1.65 to 3.6	1.65 to 5.5	IO = -60 µA	V <sub>L</sub> - 0.4	—	—	V <sub>L</sub> - 0.4	—	V	
V <sub>OLL</sub>	Low-level output voltage (I/O <sub>VL</sub> )	1.65 to 3.6	1.65 to 5.5	IO = +60 µA	—	—	0.4	—	0.4	V	
V <sub>OHC</sub>	High-level output voltage (I/O <sub>VCC</sub> )	1.65 to 3.6	1.65 to 5.5	IO = -60 µA	V <sub>CC</sub> - 0.4	—	—	V <sub>CC</sub> - 0.4	—	V	
V <sub>OLC</sub>	Low-level output voltage (I/O <sub>VCC</sub> )	1.65 to 3.6	1.65 to 5.5	IO = +60 µA	—	—	0.4	—	0.4	V	
I <sub>OE</sub>	Control input leakage current (OE)	1.65 to 3.6	1.65 to 5.5	V <sub>I</sub> = GND or V <sub>L</sub>	—	—	0.1	—	1	µA	
I <sub>IO_LKG</sub>	High impedance leakage current (I/O <sub>VL</sub> , I/O <sub>VCC</sub> )	1.65 to 3.6	1.65 to 5.5	OE = GND I/O <sub>VL</sub> = high I/O <sub>VCC</sub> = low	—	—	0.1	—	1	µA	
				OE = GND I/O <sub>VL</sub> = low I/O <sub>VCC</sub> = high	—	—	0.1	—	1	µA	

**Table 6. DC characteristics (continued)**

Symbol	Parameter	V <sub>L</sub>	V <sub>CC</sub>	Test conditions	Value					Unit	
					T <sub>A</sub> = 25 °C			-40 to 85 °C			
					Min.	Typ.	Max.	Min.	Max.		
I <sub>OFF</sub>	Partial power-down current	1.65 to 3.6	0	OE = V <sub>L</sub> or GND I/O <sub>VL</sub> = high I/O <sub>VCC</sub> = low	—	—	0.1	—	1	μA	
				OE = V <sub>L</sub> or GND I/O <sub>VL</sub> = low I/O <sub>VCC</sub> = high	—	—	0.1	—	1		
I <sub>QVCC</sub>	Quiescent supply current V <sub>CC</sub>	1.65 to 3.6	1.65 to 5.5	OE = V <sub>L</sub>	--	—	7	—	9	μA	
I <sub>QVL</sub>	Quiescent supply current V <sub>L</sub>	1.65 to 3.6	1.65 to 5.5	OE = V <sub>L</sub>	—	—	0.1	—	1	μA	
		1.65 to 3.6	0		—	—	0.1	—	1		
I <sub>Z-VCC</sub>	High impedance quiescent supply current V <sub>CC</sub>	1.65 to 3.6	1.65 to 5.5	OE = GND I/O = Hi-Z	—	—	0.1	—	1	μA	
I <sub>Z-VL</sub>	High impedance quiescent supply current V <sub>L</sub>	1.65 to 3.6	1.65 to 5.5	OE = GND I/O = Hi-Z	—	—	0.1	—	1	μA	
		1.65 to 3.6	0		—	—	0.1	—	1		

## AC characteristics

Load C<sub>L</sub> = 15 pF; driver t<sub>r</sub> = t<sub>f</sub> ≤ 6 ns over temperature range -40 °C to 85 °C.

**Table 7. AC characteristics - test conditions: V<sub>L</sub> = 1.65 - 1.95 V**

Symbol	Parameter	V <sub>CC</sub> = V <sub>L</sub> – 1.95 V		V <sub>CC</sub> = 2.3 – 2.7 V		V <sub>CC</sub> = 3.0 – 3.6 V		V <sub>CC</sub> = 4.5 – 5.5 V		Unit	
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.		
t <sub>RVCC</sub>	Rise time I/O <sub>VCC</sub>	—	5.0	—	3.2	—	2.4	—	1.4	ns	
t <sub>FVCC</sub>	Fall time I/O <sub>VCC</sub>	—	1.5	—	1.4	—	1.3	—	1.2	ns	
t <sub>RVL</sub>	Rise time I/O <sub>VL</sub>	—	2.8	—	2.7	—	2.6	—	2.6	ns	
t <sub>FVL</sub>	Fall time I/O <sub>VL</sub>	—	1.5	—	1.4	—	1.4	—	1.3	ns	
t <sub>I/OVL-VCC</sub>	Propagation delay time I/O <sub>VL-LH</sub> to I/O <sub>VCC-LH</sub> I/O <sub>VL-HL</sub> to I/O <sub>VCC-HL</sub>	t <sub>PLH</sub>	—	6.6	—	5.8	—	5.0	—	4.4	ns
		t <sub>PHL</sub>	—	4.1	—	3.8	—	3.6	—	3.4	ns

**Table 7. AC characteristics - test conditions:  $V_L = 1.65 - 1.95 \text{ V}$  (continued)**

$t_{I/OVCC-VL}$	Propagation delay time I/O <sub>VCC-LH</sub> to I/O <sub>VL-LH</sub>	$t_{PLH}$	—	4.9	—	4.4	—	4.1	—	4.4	ns
	I/O <sub>VCC-HL</sub> to I/O <sub>VL-HL</sub>	$t_{PHL}$	—	4.6	—	4.2	—	4.0	—	3.6	ns
$t_{PZL} t_{PZH}$	Output enable time	—	27	—	27	—	27	—	27	—	ns
$t_{PLZ} t_{PHZ}$	Output disable time	—	145	—	145	—	145	—	145	—	ns
$D_R$	Data rate <sup>(1)</sup>	41	—	66	—	84	—	86	—	Mbps	

1. Data rate is guaranteed based on the condition that output I/O signal rise/fall time is less than 15% of period of input I/O signal; input I/O signal is at 50% duty cycle and output I/O signal duty cycle deviation is less than  $50\% \pm 10\%$ .

**Table 8. AC characteristics - test conditions:  $V_L = 2.3 - 2.7 \text{ V}$** 

Symbol	Parameter	$V_{CC} = V_L - 2.7 \text{ V}$		$V_{CC} = 3.0 - 3.6 \text{ V}$		$V_{CC} = 4.5 - 5.5 \text{ V}$		Unit	
		Min.	Max.	Min.	Max.	Min.	Max.		
$t_{RVCC}$	Rise time I/O <sub>VCC</sub>	—	3.3	—	2.2	—	1.6	ns	
$t_{FVCC}$	Fall time I/O <sub>VCC</sub>	—	1.7	—	1.6	—	1.4	ns	
$t_{RVL}$	Rise time I/O <sub>VL</sub>	—	2.2	—	2.0	—	1.9	ns	
$t_{FVL}$	Fall time I/O <sub>VL</sub>	—	1.3	—	1.2	—	1.2	ns	
$t_{I/OVL-VCC}$	Propagation delay time I/O <sub>VL-LH</sub> to I/O <sub>VCC-LH</sub>	$t_{PLH}$	—	4.6	—	4.3	—	3.9	ns
	I/O <sub>VL-HL</sub> to I/O <sub>VCC-HL</sub>	$t_{PHL}$	—	3.6	—	3.3	—	2.9	ns
$t_{I/OVCC-VL}$	Propagation delay time I/O <sub>VCC-LH</sub> to I/O <sub>VL-LH</sub>	$t_{PLH}$	—	3.9	—	3.5	—	3.5	ns
	I/O <sub>VCC-HL</sub> to I/O <sub>VL-HL</sub>	$t_{PHL}$	—	3.6	—	3.0	—	2.5	ns
$t_{PZL} t_{PZH}$	Output enable time	—	20	—	20	—	20	ns	
$t_{PLZ} t_{PHZ}$	Output disable time	—	130	—	130	—	130		
$D_R$	Data rate <sup>(1)</sup>	84	—	85	-	88	—	Mbps	

1. Data rate is guaranteed based on the condition that output I/O signal rise/fall time is less than 15% of period of input I/O signal; input I/O signal is at 50% duty cycle and output I/O signal duty cycle deviation is less than  $50\% \pm 10\%$ .

**Table 9. AC characteristics - test conditions:  $V_L = 3.0 - 3.6 \text{ V}$** 

Symbol	Parameter	$V_{CC} = V_L - 3.6 \text{ V}$		$V_{CC} = 4.5 - 5.5 \text{ V}$		Unit	
		Min.	Max.	Min.	Max.		
$t_{RVCC}$	Rise time I/O <sub>VCC</sub>	—	1.8	—	1.7	ns	
$t_{FVCC}$	Fall time I/O <sub>VCC</sub>	—	1.3	—	1.2	ns	
$t_{RVL}$	Rise time I/O <sub>VL</sub>	—	1.6	—	1.5	ns	
$t_{FVL}$	Fall time I/O <sub>VL</sub>	—	1.1	—	1.1	ns	
$t_{I/OVL-VCC}$	Propagation delay time I/O <sub>VL-LH</sub> to I/O <sub>VCC-LH</sub>	$t_{PLH}$	—	4.1	—	4.1	ns
	I/O <sub>VL-HL</sub> to I/O <sub>VCC-HL</sub>	$t_{PHL}$	—	2.6	—	2.3	ns


**Table 9. AC characteristics - test conditions:  $V_L = 3.0 - 3.6 \text{ V}$  (continued)**

$t_{I/OVCC-VL}$	Propagation delay time I/OVCC-LH to I/OVL-LH I/OVCC-HL to I/OVL-HL	$t_{PLH}$	–	4.0	–	4.0	ns
		$t_{PHL}$	–	2.6	–	2.4	ns
$t_{PZL} t_{PZH}$		Output enable time		–	15	–	15
$t_{PLZ} t_{PHZ}$		Output disable time		–	110	–	110
$D_R$	Data rate <sup>(1)</sup>	86	–	89	–	Mbps	

1. Data rate is guaranteed based on the condition that output I/O signal rise/fall time is less than 15% of period of input I/O signal; input I/O signal is at 50% duty cycle and output I/O signal duty cycle deviation is less than  $50\% \pm 10\%$ .

## 6 Test circuit

**Figure 5. Test circuit**





**Table 10. Test circuit switches**

Test	C <sub>L</sub>	R <sub>1</sub>	Switch
t <sub>PLH</sub> , t <sub>PHL</sub>	15 pF	20 kΩ	Open
t <sub>r</sub> , t <sub>f</sub>	15 pF	20 kΩ	Open
t <sub>PZL</sub> , t <sub>PLZ</sub>	15 pF	20 kΩ	V <sub>L</sub> or V <sub>CC</sub>
t <sub>PZH</sub> , t <sub>PHZ</sub>	15 pF	20 kΩ	GND

**Table 11. Waveform symbol value**


Symbol	Driving I/O <sub>VL</sub>		Driving I/O <sub>VCC</sub>	
	1.65 V ≤ V <sub>L</sub> ≤ V <sub>CC</sub> ≤ 2.5 V	3.3 V ≤ V <sub>L</sub> ≤ V <sub>CC</sub> ≤ 5.5 V	1.65 V ≤ V <sub>L</sub> ≤ V <sub>CC</sub> ≤ 2.5 V	3.3 V ≤ V <sub>L</sub> ≤ V <sub>CC</sub> ≤ 5.5 V
V <sub>IH</sub>	V <sub>L</sub>	V <sub>L</sub>	V <sub>CC</sub>	V <sub>CC</sub>
V <sub>IM</sub>	50% V <sub>L</sub>	50% V <sub>L</sub>	50% V <sub>CC</sub>	50% V <sub>CC</sub>
V <sub>OM</sub>	50% V <sub>CC</sub>	50% V <sub>CC</sub>	50% V <sub>L</sub>	50% V <sub>L</sub>
V <sub>X</sub>	V <sub>OL</sub> + 0.15 V	V <sub>OL</sub> + 0.3 V	V <sub>OL</sub> + 0.15 V	V <sub>OL</sub> + 0.3 V
V <sub>Y</sub>	V <sub>OH</sub> - 0.15 V	V <sub>OH</sub> - 0.3 V	V <sub>OH</sub> - 0.15 V	V <sub>OH</sub> - 0.3 V

**Figure 6. Waveform - propagation delay (f = 1 MHz, 50% duty cycle)****Figure 7. Waveform - output enable and disable time (f = 1 MHz, 50% duty cycle)**

## 7 Package mechanical data


In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

**Figure 8. Package outline for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch**




**Table 12. Mechanical data for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch**


Symbol	Dimensions		
	Millimeters		
	Typ.	Min.	Max.
A	0.55	0.45	0.60
A1	0.02	0	0.05
b	0.20	0.15	0.25
D	2.60	2.50	2.70
E	1.80	1.70	1.90
e	0.40	—	—
L	0.40	0.35	0.45

**Figure 9. Footprint recommendation for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch**

7874009

Figure 10. Carrier tape for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch



**Figure 11.** Reel information for QFN16 (2.6 x 1.8 x 0.55 mm) - 0.40 mm pitch

## 8 Revision history

**Table 13. Document revision history**

Date	Revision	Changes
07-Sep-2009	1	Initial release.
14-Jun-2012	2	Updated <i>Features, Figure 1, Figure 3, Section 3.2, Section 3.3, Table 4, Table 5, Table 6, Section : AC characteristics, Table 7, Table 8, Table 9</i> , minor text corrections throughout document.

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

