P-tec Corp. Tel:(866) 695 4162
2405 Commerce Circle Tel:(719) 589 3122
Alamosa CO 81101 Fax:(719) 589 3592
www.p-tec.net

PL520 Series 5mm LED Snap-in Panel Mount Holder

Features

*Snap-in Design Requires no Hardware
*Mounting Hole 6.35 mm (0.25")
*Housing Material Black Nylon UL94V-2
*1 Yellow LED with Color Diffused Lens used
*26AWG 6" (+) Red and (-) Black Wire Leads
*RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	78mW
Reverse Voltage (<100μA)	5.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-25°C to +85°C
Storage Temperature Range	-40°C to +100°C
Soldering Temperature (1.6 mm below body)	260° for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
6" Wire Leads			nm	nm	Deg	Typ	Max	Min	Typ
PL520-1Y01-2	Yellow	GaAsP	585	590	30°	2.1	2.6	13.0	33.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.