



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

2SB1073-Q 2SB1073-R

Features

- Low collector to emitter saturation voltage $V_{CE(sat)}$
- Large peak collector current I_{CP}
- Mini power type package
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	-20	V
V_{CBO}	Collector-Base Voltage	-30	V
V_{EBO}	Emitter-Base Voltage	-7	V
I_{CP}	Peak Collector Current	-7	A
I_C	Collector Current	-4	A
P_C	Collector Dissipation	1	W
T_J	Operating Junction Temperature	150	°C
T_{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=-1mA_{dc}$, $I_B=0$)	-20	---	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=-10uA_{dc}$, $I_E=0$)	-30	---	---	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ($I_E=-10uA_{dc}$, $I_C=0$)	-7	---	---	Vdc
I_{CBO}	Collector Cutoff Current ($V_{CB}=-30V_{dc}$, $I_E=0V_{dc}$)	---	---	-100	nA _{dc}
I_{EBO}	Emitter Cutoff Current ($V_{EB}=-7V_{dc}$, $I_C=0V_{dc}$)	---	---	-100	nA _{dc}
h_{FE}	DC Current Gain (note 1) ($I_C=-2A_{dc}$, $V_{CE}=-2V_{dc}$) (note 2)	120	---	315	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=-3A_{dc}$, $I_B=-0.1A_{dc}$) (note 2)	---	-0.6	-1	Vdc
f_T	Current Gain-Bandwidth Product ($V_{CB}=-6V_{dc}$, $I_E=-50mA_{dc}$, $f=200MHz$)	---	120	---	MHz
C_{ob}	Output Capacitance ($V_{CB}=-20V_{dc}$, $f=1.0MHz$, $I_E=0$)	---	40	---	pF



Note: 1. h_{FE} Rank Classification

Rank	Q	R
h_{FE}	120~205	180~315
Marking Symbol	IQ	IR

2. Pulse measurement

Silicon PNP epitaxial planer Transistors

SOT-89




1.BASE
2.COLLECTOR
3.EMITTER


DIM	DIMENSINS				NOTES
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.173	.181	4.39	4.60	
B	.063	.071	1.60	1.80	
C	.154	.165	3.91	4.25	
D	.031	.039	0.80	1.00	
E	.092	.100	2.34	2.54	
F	.118	-----	3.00	-----	TYP
G	.013	.019	0.33	0.48	
H	.015	.021	0.38	0.53	
J	.015	.016	0.38	0.41	
K	.055	.063	1.40	1.60	

2SB1073


$P_C - T_a$




$I_C - V_{CE}$




$I_C - V_{BE}$




$V_{CE(sat)} - I_C$



$h_{FE} - I_C$



$C_{ob} - V_{CB}$





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape & Reel; 1 Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com