




1. Mechanical Dimensions:




Top view



Side view




Bottom view



Typical Pad Layout

2. Schematic:



3. Electrical Specifications:

OCL: 2.20uH±20% @100KHz 0.25V, 0.0Adc

Q: tbd Min @100KHz 0.25V

Isat: 14.0Adc (Based on 20% Typ drop in OCL)

Irms: 8.0Adc (Based on 40°C Temp Rise Typ)

DCR: 17.7 mOhms ±10%

Notes:

- Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
- Flammability: UL94V-0
- ASTM oxygen index: > 28%
- Insulation System: Class F 155°C. UL file E151556
- Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
- Storage Temperature Range: -55°C to +125°C
- Aqueous wash compatible
- SMD Lead Coplanarity: ±0.004"(0.102mm)
- Electrical and mechanical specifications 100% tested
- RoHS Compliant Component

PRELIMINARY

DOC. REV: A/1

XFMRs Inc. www.XFMRs.com	Title: SMD INDUCTORS		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFHCL6MD-2R2M		REV. A
	DWN.	Feng	Jul-10-12
SHEET 1 OF 1	CHK.	YK Liao	Jul-10-12
	APP.	BSJ	Jul-10-12