

NPN SILICON MICROWAVE POWER TRANSISTORS

PRODUCT DATA SHEET

FEATURES:

- High Output Power
10 W @ 1.8 GHz
- High Gain Bandwidth Product
 $f_t = 6.0 \text{ GHz typ @ } I_C = 1.6 \text{ A}$
- High Gain
 $G_{PE} = 9.0 \text{ dB @ } 1.8 \text{ GHz}$
- Gold Metallization System
- High thermal efficiency BeO 6 Lead Flange package (package 36)



DESCRIPTION AND APPLICATIONS:

Bipolarics' BPT1819E10 is a high performance silicon bipolar transistor intended for linear power applications at frequencies of 1.8 to 1.9 GHz. Typical applications include amplifiers in aeronautical, maritime and personal communication applications. The BPT1819E10 is bonded common emitter for linear applications. Linear output power of 10 Watts can be achieved. BeO flange packaging makes this device excellent for industrial and military products. Uniformity and reliability are assured by the use of ion implanted junctions, ion implanted ballast resistors and gold metallization.

Absolute Maximum Ratings:

SYMBOL	PARAMETERS	RATING	UNITS
V_{CES}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	20	V
V_{EBO}	Emitter-Base Voltage	3.0	V
I_C	Collector Current	3.2	A
T_J	Junction Temperature	200	°C
T_{STG}	Storage Temperature	-65 to 200	°C
θ_{JC}	Thermal Resistance	4.5	C/W

PERFORMANCE DATA:

- Electrical Characteristics ($T_A = 25^\circ\text{C}$)

SYMBOL	PARAMETERS & CONDITIONS		UNIT	MIN.	TYP.	MAX.
	$V_{CE} = 15\text{V}, I_C = 1.6 \text{ A}, \text{Class A, Common Emitter unless stated}$					
BV _{CEO}	Collector-Emitter Breakdown Voltage	$I_C = 0.1 \text{ mA}$	V	20		
P _{1dB}	Output Power at 1dB compression	$f = 1.8 \text{ GHz}$	W		10.0	
G _{PE}	Class A P _{OUT} = 12 W	$f = 1.8 \text{ GHz}$	dB		9.0	
η	Efficiency:	Class A Class C	%		30 65	
h _{FE}	Forward Current Transfer Ratio: $V_{CE} = 8.0\text{V}, I_C = 1.2 \text{ A}$	$f = 1.0 \text{ MHz}$		20	60	100
C _{CB}	Collector Base Capacitance:	$f = 1.0 \text{ MHz}$ $I_E = 0$	pF		24.0	
P _T	Total Power Dissipation		W			36