

**isc N-Channel MOSFET Transistor**

**IRF40B207, IIRF40B207**

**• FEATURES**

- Static drain-source on-resistance:  
 $R_{DS(on)} \leq 4.5m\Omega$
- Enhancement mode
- Fast Switching Speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**• DESCRIPTION**



- reliable device for use in a wide variety of applications

**• ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{DSS}$	Drain-Source Voltage	40	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current-Continuous	95	A
$I_{DM}$	Drain Current-Single Pulsed	380	A
$P_D$	Total Dissipation @ $T_c=25^\circ C$	83	W
$T_j$	Max. Operating Junction Temperature	175	$^\circ C$
$T_{stg}$	Storage Temperature	-55~175	$^\circ C$

**• THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th(ch-c)}$	Channel-to-case thermal resistance	1.8	$^\circ C/W$
$R_{th(ch-a)}$	Channel-to-ambient thermal resistance	62	$^\circ C/W$



**isc N-Channel MOSFET Transistor**
**IRF40B207, IIRF40B207**
**ELECTRICAL CHARACTERISTICS**

 T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V; I <sub>D</sub> =250 μ A	40			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> ; I <sub>D</sub> =50 μ A	2.2		3.9	V
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> =10V; I <sub>D</sub> =57A			4.5	mΩ
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> =±20V			±0.1	μ A
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =40V; V <sub>GS</sub> = 0V			1.0	μ A
V <sub>SD</sub>	Diode forward voltage	I <sub>S</sub> =57A, V <sub>GS</sub> = 0 V			1.3	V