
## KEMET Part Number: SMR15225J63B12L16.5CBULK

(F211BM225J063ALG5C)



Film, Metallized PPS, Commercial Grade, SMR/F211, 2.2 uF, 5%, 63 V, 125C, Lead Spacing = 15mm



Dimensions	
L	18mm MAX
Н	15mm MAX
Т	8mm MAX
S	15mm +/-0.4mm
LL	16.5mm +/-0.5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Packaging Specifications		
Packaging:	Bulk	
Packaging Quantity:	400	

General Information	
Dielectric:	Metallized PPS
Style:	Radial
Series:	SMR/F211
RoHS:	Yes
Lead:	Wire Leads
Miscellaneous:	The rated voltage decreases 2%/ C between +125C and +150C
Notes:	Case Size = BM

Specifications		
Capacitance:	2.2 uF	
Capacitance Tolerance:	5%	
Voltage DC:	63 VDC	
Voltage AC:	40 VAC	
Temperature Range:	-55/+150C	
Rated Temperature:	125C	
Dissipation Factor:	0.15% 1kHz, 0.35% 10kHz	
Insulation Resistance:	2.27273 GOhms	
Max dVdt:	6 V	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

